



- Double Pole Switching
- Neon Indicator
- Highly Polished Chrome Finish Rocker

Product Specification Data

Revision Date: 17/12/2021

Product Standard/s	BS EN 60669-1
Terminal Capacity L&N	3 x 2.5, 2 x 4.0, 1 x 6.0, 1 x 10.0, 1 x 16.0 mm ²
Terminal Capacity E	3 x 2.5, 2 x 4.0, 1 x 6.0, 1 x 10.0, 1 x 16.0 mm ²
Frequency	50 Hz
CE Conformity	Yes
WEEE Symbol	Yes
UKCA Conformity	Yes
Wiring system	2-pole switch
Method of operation	Rocker/button
Assembly arrangement	Control element
Number of modules (module system)	0
Push button switch	Yes
Number of rockers	1
Mounting method	Flush mounted (plaster)
Type of fastening	Screw mounting
With mounting plate	No
Material	Metal
Material quality	Other
Halogen free	Yes
Surface protection	Other
Surface finishing	Matt
Colour	Aluminium
Illumination	Yes
Function lighting	Illuminated (on)
Type of lighting	Not included
Suitable for degree of protection (IP)	IP2X
Nominal voltage	250 V
Rated current	45 A
Connection type	Screwed terminal

Min. depth of built-in installation box

47 mm

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.



Electrium Sales Limited, Walkmill Lane, Cannock WS11 0XE
01543 455000 www.electrium.co.uk info@electrium.co.uk