


List No. 1522/1SC SCREWLESS & FLATPLATE INTERIORS

45A Cooker Control Unit With 13A Socket Interior Satin Chrome Finish Rockers



• Black Interior



| Product Standard/s BS 4177, BS 1363-2 Terminal Capacity L&N 2 x 6.0, 1 x 10, 1 x 16 mm² Terminal Capacity E 2 x 6.0, 1 x 10.0, 1 x 16.0 mm² Frequency 50 Hz CE Conformity Yes WEEE Symbol Yes UKCA Conformity Yes Wiring system 2-pole switch Method of operation Rocker/button Assembly arrangement Control element Number of modules (module system) 0 Push button switch Yes Number of rockers 2 Quantity Flush mounted (plaster) Type of fastening Screw mounting With mounting plate No Material Metal Material quality Other Halogen free Yes Surface protection Other Surface finishing Matt Colour Aluminium Illumination No Function lighting Other Type of lighting Not included Suitable for degree of protecti | Product Specification Data | Revision Date: 15/10/2021 |
|--|--|---|
| Terminal Capacity E 2 x 6.0, 1 x 10.0, 1 x 16.0 mm² Frequency 50 Hz CE Conformity Yes WEEE Symbol Yes UKCA Conformity Yes Wiring system 2-pole switch Method of operation Rocker/button Assembly arrangement Control element Number of modules (module system) 0 Push button switch Yes Number of rockers 2 Mounting method Flush mounted (plaster) Type of fastening Screw mounting With mounting plate No Material Metal Material quality Other Halogen free Yes Surface protection Other Surface finishing Matt Colour Aluminium Illumination No Function lighting Not included Suitable for degree of protection (IP) IP2X Nominal voltage 250 V Rated current 45 A | Product Standard/s | BS 4177, BS 1363-2 |
| Frequency CE Conformity Yes WEEE Symbol Yes UKCA Conformity Yes Wiring system 2-pole switch Method of operation Assembly arrangement Number of modules (module system) Push button switch Yes Number of rockers 2 Mounting method Flush mounted (plaster) Type of fastening Screw mounting With mounting plate Material Material Material quality Halogen free Surface protection Surface finishing Colour Alumination Function lighting Surbace Suitable for degree of protection (IP) Nominal voltage Rated current Rocker/button Yes Control element Control element No Control element No No Function lighting No No No Pattorion lighting Surface for degree of protection (IP) P2X Nominal voltage Rated current Yes Surface for degree of protection (IP) Rated current Pass Pass Pass Pass Pass Pass Pass Pas | Terminal Capacity L&N | 2 x 6.0, 1 x 10, 1 x 16 mm ² |
| CE Conformity Yes WEEE Symbol Yes UKCA Conformity Yes Wiring system 2-pole switch Method of operation Rocker/button Assembly arrangement Control element Number of modules (module system) 0 Push button switch Yes Number of rockers 2 Mounting method Flush mounted (plaster) Type of fastening Screw mounting With mounting plate No Material Metal Material quality Other Halogen free Yes Surface protection Other Surface finishing Matt Colour Aluminium Illumination No Function lighting Other Type of lighting Not included Suitable for degree of protection (IP) IP2X Nominal voltage 250 V Rated current 45 A | Terminal Capacity E | 2 x 6.0, 1 x 10.0, 1 x 16.0 mm ² |
| WEEE Symbol Yes UKCA Conformity Yes Wiring system 2-pole switch Method of operation Rocker/button Assembly arrangement Control element Number of modules (module system) 0 Push button switch Yes Number of rockers 2 Mounting method Flush mounted (plaster) Type of fastening Screw mounting With mounting plate No Material Metal Material quality Other Halogen free Yes Surface protection Other Surface finishing Matt Colour Aluminium Illumination No Function lighting Other Type of lighting Not included Suitable for degree of protection (IP) IP2X Nominal voltage 250 V Rated current 45 A | Frequency | 50 Hz |
| UKCA Conformity Wiring system 2-pole switch Method of operation Assembly arrangement Control element Number of modules (module system) Push button switch Yes Number of rockers 2 Mounting method Type of fastening With mounting plate No Material Metal Material quality Halogen free Surface protection Surface finishing Colour Aluminium Illumination Function lighting Not included Suitable for degree of protection (IP) Rated current Passembly arrangement Control element Rocker/button Rocker/button Rocker/button Rocker/button Rocker/button Rocker/button Rocker/button Surface finishing Other Aluminium No Purction lighting Not included Suitable for degree of protection (IP) Rated current Pass | CE Conformity | Yes |
| Wiring system Method of operation Assembly arrangement Number of modules (module system) Push button switch Number of rockers Number of rockers Push button switch Number of rockers Push button switch Number of rockers Push mounted (plaster) Type of fastening Screw mounting With mounting plate No Material Metal Material quality Other Halogen free Surface protection Surface finishing Matt Colour Aluminium Illumination No Function lighting Other Type of lighting Suitable for degree of protection (IP) Nominal voltage Rated current Push modules (module system) Rocker/button Rocker/Bu | WEEE Symbol | Yes |
| Method of operationRocker/buttonAssembly arrangementControl elementNumber of modules (module system)0Push button switchYesNumber of rockers2Mounting methodFlush mounted (plaster)Type of fasteningScrew mountingWith mounting plateNoMaterialMetalMaterial qualityOtherHalogen freeYesSurface protectionOtherSurface finishingMattColourAluminiumIlluminationNoFunction lightingOtherType of lightingNot includedSuitable for degree of protection (IP)IP2XNominal voltage250 VRated current45 A | UKCA Conformity | Yes |
| Assembly arrangement Number of modules (module system) Push button switch Yes Number of rockers 2 Mounting method Flush mounted (plaster) Type of fastening Screw mounting With mounting plate No Material Metal Material quality Other Halogen free Surface protection Surface finishing Colour Aluminium Illumination Function lighting Type of lighting Suitable for degree of protection (IP) Rush Non No Raterial Not included Raterial Rate | Wiring system | 2-pole switch |
| Number of modules (module system) 0 Push button switch Yes Number of rockers 2 Mounting method Flush mounted (plaster) Type of fastening Screw mounting With mounting plate No Material Metal Material quality Other Halogen free Yes Surface protection Other Surface finishing Matt Colour Aluminium Illumination No Function lighting Other Type of lighting Not included Suitable for degree of protection (IP) IP2X Nominal voltage 250 V Rated current 45 A | Method of operation | Rocker/button |
| Push button switchYesNumber of rockers2Mounting methodFlush mounted (plaster)Type of fasteningScrew mountingWith mounting plateNoMaterialMetalMaterial qualityOtherHalogen freeYesSurface protectionOtherSurface finishingMattColourAluminiumIlluminationNoFunction lightingOtherType of lightingNot includedSuitable for degree of protection (IP)IP2XNominal voltage250 VRated current45 A | Assembly arrangement | Control element |
| Number of rockers 2 Mounting method Flush mounted (plaster) Type of fastening Screw mounting With mounting plate No Material Metal Material quality Other Halogen free Yes Surface protection Other Surface finishing Matt Colour Aluminium Illumination No Function lighting Other Type of lighting Not included Suitable for degree of protection (IP) IP2X Nominal voltage 250 V Rated current 45 A | Number of modules (module system) | 0 |
| Mounting method Flush mounted (plaster) Type of fastening Screw mounting With mounting plate No Material Metal Material quality Other Halogen free Yes Surface protection Other Surface finishing Matt Colour Aluminium Illumination No Function lighting Other Type of lighting Not included Suitable for degree of protection (IP) Rated current 45 A | Push button switch | Yes |
| Type of fastening With mounting plate No Material Metal Material quality Other Halogen free Yes Surface protection Surface finishing Matt Colour Aluminium Illumination Function lighting Type of lighting Suitable for degree of protection (IP) Rated current Screw mounting No Metal No Metal Other Yes Author Aluminium No Function lighting Not included Suitable for degree of protection (IP) Rated current 45 A | Number of rockers | 2 |
| With mounting plate Material Material quality Other Halogen free Yes Surface protection Other Surface finishing Matt Colour Aluminium Illumination Function lighting Type of lighting Suitable for degree of protection (IP) Nominal voltage Rated current No Metal Metal Metal Metal Metal Aluminium Other Surface finishing Matt Colour Aluminium No Function lighting Not included Suitable for degree of protection (IP) Rated current 45 A | Mounting method | Flush mounted (plaster) |
| MaterialMetalMaterial qualityOtherHalogen freeYesSurface protectionOtherSurface finishingMattColourAluminiumIlluminationNoFunction lightingOtherType of lightingNot includedSuitable for degree of protection (IP)IP2XNominal voltage250 VRated current45 A | Type of fastening | Screw mounting |
| Material qualityOtherHalogen freeYesSurface protectionOtherSurface finishingMattColourAluminiumIlluminationNoFunction lightingOtherType of lightingNot includedSuitable for degree of protection (IP)IP2XNominal voltage250 VRated current45 A | With mounting plate | No |
| Halogen free Yes Surface protection Other Surface finishing Matt Colour Aluminium Illumination No Function lighting Other Type of lighting Not included Suitable for degree of protection (IP) IP2X Nominal voltage 250 V Rated current 45 A | Material | Metal |
| Surface protection Surface finishing Matt Colour Aluminium Illumination No Function lighting Other Type of lighting Not included Suitable for degree of protection (IP) Nominal voltage Rated current Other 45 A | Material quality | Other |
| Surface finishing Colour Aluminium Illumination No Function lighting Other Type of lighting Not included Suitable for degree of protection (IP) IP2X Nominal voltage 250 V Rated current 45 A | Halogen free | Yes |
| Colour Aluminium Illumination No Function lighting Other Type of lighting Not included Suitable for degree of protection (IP) IP2X Nominal voltage 250 V Rated current 45 A | Surface protection | Other |
| Illumination No Function lighting Other Type of lighting Not included Suitable for degree of protection (IP) IP2X Nominal voltage 250 V Rated current 45 A | Surface finishing | Matt |
| Function lighting Type of lighting Not included Suitable for degree of protection (IP) IP2X Nominal voltage 250 V Rated current 45 A | Colour | Aluminium |
| Type of lighting Suitable for degree of protection (IP) Nominal voltage 250 V Rated current A5 A | Illumination | No |
| Suitable for degree of protection (IP) Nominal voltage 250 V Rated current 45 A | Function lighting | Other |
| Nominal voltage 250 V Rated current 45 A | Type of lighting | Not included |
| Rated current 45 A | Suitable for degree of protection (IP) | IP2X |
| | Nominal voltage | 250 V |
| Connection type Screwed terminal | Rated current | 45 A |
| | Connection type | Screwed terminal |

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.

| Product Specification Data (cont) | Revision Date: 15/10/2021 |
|---|---------------------------|
| Built-in depth | 24 mm |
| Min. depth of built-in installation box | 47 mm |

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.

