



- For Powerstar VM160 Panel Boards
- Use in conjunction with inter-connection kit
- Electronic trip unit (LI) for system protection, with adjustable electronic elements
- Requires interconnection kit to connect to main busbars

Product Specification Data

Revision Date: 06/09/2022

| | |
|--|----------------------------|
| Rated permanent current I_n | 400 A |
| Rated voltage | 400 V |
| Rated short-circuit breaking capacity I_{cu} at 400 V, 50 Hz | 55 kA |
| Overload release current setting | 160-400 A |
| Integrated earth fault protection | No |
| Type of electrical connection of main circuit | Other |
| Device construction | Complete device in housing |
| Suitable for DIN rail (top hat rail) mounting | No |
| DIN rail (top hat rail) mounting optional | No |
| Number of auxiliary contacts as normally closed contact | 0 |
| Number of auxiliary contacts as normally open contact | 0 |
| Number of auxiliary contacts as change-over contact | 0 |
| With switched-off indicator | No |
| With integrated under voltage release | No |
| Number of poles | 3 |
| Position of connection for main current circuit | Other |
| Type of control element | Toggle |
| Complete device with protection unit | Yes |
| Motor drive integrated | No |
| Motor drive optional | Yes |
| Degree of protection (IP) | IP40 |
| CE Conformity | Yes |
| WEEE Symbol | Yes |
| UKCA Conformity | Yes |

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.