



- For Powerstar VM160 Panel Boards
- Use in conjunction with inter-connection kit
- Electronic trip unit (LI) for system protection, with adjustable electronic elements
- Requires interconnection kit to connect to main busbars

Product Specification Data

Revision Date: 06/09/2022

Rated permanent current I_u	630 A
Rated voltage	400 V
Rated short-circuit breaking capacity I_{cu} at 400 V, 50 Hz	55 kA
Overload release current setting	250-630 A
Integrated earth fault protection	No
Type of electrical connection of main circuit	Other
Device construction	Complete device in housing
Suitable for DIN rail (top hat rail) mounting	No
DIN rail (top hat rail) mounting optional	No
Number of auxiliary contacts as normally closed contact	0
Number of auxiliary contacts as normally open contact	0
Number of auxiliary contacts as change-over contact	0
With switched-off indicator	No
With integrated under voltage release	No
Number of poles	4
Position of connection for main current circuit	Other
Type of control element	Toggle
Complete device with protection unit	Yes
Motor drive integrated	No
Motor drive optional	Yes
Degree of protection (IP)	IP40
CE Conformity	Yes
WEEE Symbol	Yes
UKCA Conformity	Yes

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.