



- 16W 250A 3P+N Type 'B' distribution board
- TP or 4P Switch disconnecter, MCCB, or direct connection incomer options available
- Accepts all Crabtree Loadstar 10kA final circuit protection devices; Single Pole and Triple Pole Type B, C, and D MCBs (6A to 80A) and Single Pole Type B and C RCBOs (6A to 50A)
- Accepts the Crabtree LS250MPKIT (Pulsed Output/Modbus RTU), LS250MIDMPKIT (MID) integral incoming meter kits or LS250SPKITL integral Type 2 surge protection kit
- RAL 7035 Grey powder coat finish. Designed and manufactured in the UK to BS EN 61439-3

### Product Specification Data

Revision Date: 05/12/2022

Mounting method	Surface mounted (plaster)
Number of phases	3
Main switch rated current	250 A
Material housing	Steel
Degree of protection (IP)	IP31
Height	1092 mm
Width	430 mm
Depth	155 mm
Extension possible	Yes
With transparent cover	No
Lockable	Yes
Product Standard/s	BS EN 61439-3
Frequency	50 Hz
CE Conformity	Yes
WEEE Symbol	Yes
UKCA Conformity	Yes
Number of ways (Type 'B' boards)	16
Amperage	250 A
Pole Configuration	TPN
Operating Voltage	400 V
Type of Current	AC
Busbar type	FIXED SOLID COPPER
Colour RAL	7035

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.