



- 8W Main switch only meter cabinet consumer unit
- Includes a 100A double pole main switch upon a flexible busbar
- Accepts Loadstar final circuit protection devices; MCBs and RCBOs
- Accepts the Crabtree miniature type 2 SPD, CRT2SPD3W/1
- Constructed from a full metal enclosure with angled visor and is suitable for mounting upon 273mm fixing centres

Product Specification Data

Revision Date: 11/07/2022

Mounting method	Other
Number of phases	1
Protection	Miniature- / earth leakage circuit breaker
Total number of groups	1
Number of poles main switch	2
Main switch rated current	100 A
Over voltage protection	No
Material housing	Steel
Degree of protection (IP)	IP2XC
Height	257 mm
Width	289 mm
Width in number of modular spacings	10
Depth	119 mm
Extension possible	No
With transparent cover	No
Lockable	No
Product Standard/s	BS EN 61439-3
Frequency	50 Hz
CE Conformity	Yes
WEEE Symbol	Yes
UKCA Conformity	Yes
Amperage	100 A
Operating Voltage	230 V
Type of Current	AC
Consumer Unit Type	Main switch only
Total final circuit modular ways	8
Busbar type	Flexible
Main switch rating	100 A
Main switch final circuit modular ways	8

Bespoke application	Meter cabinet
Colour RAL	9010

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.



Electrium Sales Limited, Walkmill Lane, Cannock WS11 0XE
01543 455000 www.electrium.co.uk info@electrium.co.uk