



**18PSC10-S513A
SHOWN**

- Type 'A' 1P+N Distribution board
- Designed and manufactured in the UK to BS EN61439-3
- RAL 7035 Grey powder coat finish
- Comes with 2 x 80A 30ma 2P RCCB incomers
- 125A 2P switch disconnecter included to isolate all outgoing Ways

Product Specification Data		Revision Date: 15/10/2021
Mounting method	Surface mounted (plaster)	
Number of phases	2	
Number of poles main switch	2	
Main switch rated current	125 A	
Material housing	Steel	
Degree of protection (IP)	IP31	
Height	261 mm	
Width	343 mm	
Depth	131 mm	
Extension possible	No	
Lockable	Yes	
Product Standard/s	BS EN 61439-3	
Frequency	50 Hz	
CE Conformity	Yes	
WEEE Symbol	Yes	
UKCA Conformity	Yes	
Number of rows (Type 'A' boards)	1	
Number of ways (Type 'A' boards)	10	
Amperage	125 A	
Fault Rating	10	
Pole Configuration	DPN	
Operating Voltage	240 V	
Type of Current	AC	
Busbar type	COMB BUSBAR	
Colour RAL	7035	

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.