



- Type 'B' 3P+N Distribution board
- Designed and manufactured in the UK to BS EN61439-3
- RAL 7035 Grey powder coat finish
- Integral metering options available

| Product Specification Data       |                           | Revision Date: 15/10/2021 |
|----------------------------------|---------------------------|---------------------------|
| Mounting method                  | Surface mounted (plaster) |                           |
| Number of phases                 | 3                         |                           |
| Number of poles main switch      | 3                         |                           |
| Main switch rated current        | 250 A                     |                           |
| Material housing                 | Steel                     |                           |
| Degree of protection (IP)        | IP31                      |                           |
| Height                           | 1308 mm                   |                           |
| Width                            | 430 mm                    |                           |
| Depth                            | 155 mm                    |                           |
| Extension possible               | Yes                       |                           |
| Lockable                         | Yes                       |                           |
| Product Standard/s               | BS EN 61439-3             |                           |
| Frequency                        | 50 Hz                     |                           |
| CE Conformity                    | Yes                       |                           |
| WEEE Symbol                      | Yes                       |                           |
| UKCA Conformity                  | Yes                       |                           |
| Number of ways (Type 'B' boards) | 24                        |                           |
| Amperage                         | 250 A                     |                           |
| Fault Rating                     | 25                        |                           |
| Pole Configuration               | TPN                       |                           |
| Operating Voltage                | 415 V                     |                           |
| Type of Current                  | AC                        |                           |
| Busbar type                      | FIXED SOLID COPPER        |                           |
| Colour RAL                       | 7035                      |                           |

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.