



- 16W Main switch only Type 'A' distribution board
- Includes a 100A main switch with twin line and neutral supply terminals and a 100A fixed busbar assembly
- Accepts Crabtree Loadstar 10kA final circuit protection devices; SP MCBs from 6A to 63A and RCBOs from 6A to 50A
- Accepts the Crabtree miniature type 2 SPD CRT2SPD3W/1
- RAL 7035 Grey powder coat finish. Designed and manufactured in the UK to BS EN 61439-3

Product Specification Data

Revision Date: 12/06/2023

Mounting method	Surface mounted (plaster)
Number of phases	2
Number of poles main switch	1
Main switch rated current	100 A
Material housing	Steel
Degree of protection (IP)	IP31
Height	235 mm
Width	437 mm
Depth	133 mm
Extension possible	No
With transparent cover	No
Lockable	Yes
Product Standard/s	BS EN 61439-3
Frequency	50 Hz
CE Conformity	Yes
WEEE Symbol	Yes
UKCA Conformity	Yes
Number of rows (Type 'A' boards)	1
Number of ways (Type 'A' boards)	16
Amperage	100 A
Pole Configuration	SPN
Operating Voltage	230 V
Type of Current	AC
Busbar type	COMB BUSBAR
Colour RAL	7035

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.