

List No. 2400W/BZ RAISED DECORATIVE

2 Gang 400 Watt Dimmer Bronze Finish



- Intelligent Dimming Technology
- Bronze Finish

| roduct Specification Data | Revision Date: 15/10/2021 |
|--|----------------------------------|
| Product Standard/s | BS EN 60669-2-1 |
| Terminal Capacity L&N | 2 x 1.0, 1 x 2.5 mm ² |
| Frequency | 50 Hz |
| CE Conformity | Yes |
| WEEE Symbol | Yes |
| UKCA Conformity | Yes |
| Wiring system | Two-way switch |
| Method of operation | Turn button |
| Assembly arrangement | Basic element |
| Number of modules (module system) | 0 |
| Push button switch | Yes |
| Number of rockers | 2 |
| Mounting method | Flush mounted (plaster) |
| Type of fastening | Screw mounting |
| With mounting plate | Yes |
| Material | Metal |
| Material quality | Other |
| Halogen free | Yes |
| Surface protection | Lacquered |
| Surface finishing | Matt |
| Colour | Bronze |
| Illumination | No |
| Function lighting | Other |
| Type of lighting | Incandescent lamp |
| Suitable for degree of protection (IP) | IP2X |
| Nominal voltage | 250 V |
| Rated current | 1.6 A |
| Connection type | Screwed terminal |
| Width of device | 86 mm |

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.

| Product Specification Data (cont) | Revision Date: 15/10/2021 |
|---|---------------------------|
| Height of device | 86 mm |
| Min. depth of built-in installation box | 35 mm |

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.

