



- Two module, Bi-Directional RCBO (wire in wire out)
- 32A C curve (MCB), 30mA Type A (RCD)
- Single pole with switched neutral

Product Specification Data		Revision Date: 07/02/2024
Number of poles (total)	2	
Number of protected poles	1	
Rated voltage	230 V	
Rated insulation voltage $U_i$	400 V	
Rated impulse withstand voltage $U_{imp}$	4 kV	
Rated current	32 A	
Rated fault current	0.03 A	
Leakage current type	A	
Current limiting class	3	
Rated short-circuit breaking capacity $I_{cn}$ according to EN 61009-1	6 kA	
Disconnection characteristic	Undelayed	
Voltage type	AC	
Frequency	50 Hz	
Release characteristic	C	
Concurrently switching neutral conductor	Yes	
With interlocking device	No	
Over voltage category	3	
Ambient temperature during operating	-5 - 40 °C	
Width in number of modular spacings	2	
Built-in depth	73 mm	
Flush-mounted installation	No	
Anti- nuisance tripping version	No	
Degree of protection (IP)	IP20	
Connectable conductor cross section solid-core	.75-16 mm <sup>2</sup>	
Connectable conductor cross section multi-wired	.75-16 mm <sup>2</sup>	
Product Standard/s	IEC 61009-1	
CE Conformity	Yes	
WEEE Symbol	Yes	

Product Specification Data (cont)		Revision Date: 07/02/2024
UKCA Conformity		Yes