List No. 4013/3/AC

CAPITAL

32A 1 Gang Double Pole Control Switch With Neon Printed 'Air Conditioner'

- Double Pole Switching
- Fully Rated to 32A
- Neon Indicator

Product Specification Data	Revision Date: 11/10/2024
Product Standard/s	BS EN 60669-1
Terminal Capacity L&N	3 x 2.5, 2 x 4.0, 1 x 10.0 mm²
Terminal Capacity E	3 x 2.5, 2 x 4.0, 1 x 10.0 mm²
Frequency	50 Hz
LRV Value	74
Printing	Air Conditioner
CE Conformity	Yes
WEEE Symbol	Yes
UKCA Conformity	Yes
Wiring system	2-pole switch
Method of operation	Rocker/button
Assembly arrangement	Control element
Number of modules (module system)	0
Push button switch	Yes
Number of rockers	1
Mounting method	Flush-mounted
Type of fastening	Screw mounting
With mounting plate	Yes
Material	Plastic
Material quality	Other
Halogen free	Yes
Surface protection	Other
Surface finishing	Glossy
Colour	White
Illumination	Yes
Function lighting	Illuminated (on)
Suitable for degree of protection (IP)	IP2X
Nominal voltage	250 V
Rated current	32 A

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.

Connection type	Screwed terminal
Device width	86 mm
Device height	86 mm
Min. depth of built-in installation box	25 mm

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.

Electrium Sales Limited, Walkmill Lane, Cannock WS11 0XE
01543 455000 www.electrium.co.uk info@electrium.co.uk