List No. 4021/3PBG

CAPITAL

20A 1 Gang Double Pole Metalclad Switch With Neon & Cord Outlet

- Double Pole Switching
- Neon Indicator
- 250W SBL LED Load

Product Specification Data	Revision Date: 11/10/2024
Product Standard/s	BS EN 60669-1
Terminal Capacity L&N	3 x 2.5, 2 x 4.0, 1 x 6.0 mm²
Terminal Capacity E	3 x 1.5, 3 x 2.5, 2 x 4.0 mm²
Frequency	50 Hz
LRV Value	34
CE Conformity	Yes
WEEE Symbol	Yes
UKCA Conformity	Yes
Wiring system	2-pole switch
Method of operation	Rocker/button
Assembly arrangement	Control element
Number of modules (module system)	0
Push button switch	Yes
Number of rockers	1
Mounting method	Surface mounted
Type of fastening	Screw mounting
With mounting plate	Yes
Material	Metal
Material quality	Other
Halogen free	Yes
Surface protection	Lacquered
Surface finishing	Glossy
Colour	Grey
Illumination	Yes
Function lighting	Illuminated (on)
Suitable for degree of protection (IP)	IP2X
Nominal voltage	250 V
Rated current	20 A
Connection type	Screwed terminal

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.

Device width	86.7 mm
Device height	86.7 mm
Min. depth of built-in installation box	44 mm

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.

Electrium Sales Limited, Walkmill Lane, Cannock WS11 0XE
01543 455000 www.electrium.co.uk info@electrium.co.uk