

## List No. 4314/USBC/BZ RAISED DECORATIVE

13A 1 Gang Single Pole Switched Socket with Type A and Type C 20W USB Bronze



- Type A and Type C USB Connection
- Voltage Variation 5V to 12V
- Maximum 20 Watts
- Supports PD, PPS and QC Charging Protocols
- Bronze Finish

Product Specification Data	Revision Date: 11/10/2024
Product Standard/s	BS1363-2, BSEN 62368-1
Terminal Capacity L&N	3 x 1.5, 3 x 2.5, 2 x 4.0 mm <sup>2</sup>
Terminal Capacity E	3 x 1.5, 3 x 2.5, 2 x 4.0 mm <sup>2</sup>
CE Conformity	Yes
WEEE Symbol	Yes
G Mark	Yes
UKCA Conformity	Yes
Operating voltage	250 V
Frequency	50 Hz
Max. output current	3250 mA
Mounting method	Flush-mounted
Colour	Bronze
Min. depth of built-in installation box	25 mm

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.



**Electrium Sales Limited,** Walkmill Lane, Cannock WS11 0XE 01543 455000 www.electrium.co.uk info@electrium.co.uk