



- Fully Rated to 13A
- Safety Shutter System
- Highly Polished Chrome Finish
- Black Interior

Product Specification Data		Revision Date: 11/10/2024
Product Standard/s	BS 1363-2	
Terminal Capacity L&N	3 x 1.5, 3 x 2.5, 2 x 4.0 mm ²	
Terminal Capacity E	3 x 1.5, 3 x 2.5, 2 x 4.0 mm ²	
Frequency	50 Hz	
CE Conformity	Yes	
WEEE Symbol	Yes	
UKCA Conformity	Yes	
Model	British Standard	
Number of active contacts (round)	0	
Number of active contacts (flat)	3	
With signal lamp	No	
Number of units	1	
Number of modules (module system)	0	
Number of socket outlets switchable	2	
Number of phases	2	
Imprint/indication	Other	
Connection type	Screwed terminal	
With hinged lid	No	
With enhanced contact protection	Yes	
Label space/information surface	Yes	
Colour	Chrome	
Lockable	No	
Insulated mounting	No	
With function lighting	No	
Fault current protection	No	
Special power supply	No special power supply	
Mounting method	Surface mounted	
Type of fastening	Mounting with screw	
Material	Metal	

Product Specification Data (cont)		Revision Date: 11/10/2024
Material quality	Other	
Halogen free	Yes	
Surface protection	Other	
Surface finishing	Glossy	
Anti-bacterial treatment	No	
With on/off switch	Yes	
Nominal current	13 A	
Nominal voltage	250 V	
Suitable for degree of protection (IP)	IP2X	
Impact strength	IK02	
Device width	146 mm	
Device height	86 mm	
Device depth	31 mm	
Min. depth of built-in installation box	25 mm	

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.



Electrium Sales Limited, Walkmill Lane, Cannock WS11 0XE
01543 455000 www.electrium.co.uk info@electrium.co.uk