



- All metal meter cabinet consumer unit
- Flexible busbar assembly
- 10W Dual RCD
- 430mm fixing centres

Product Specification Data		Revision Date: 15/10/2021
Mounting method	Other	
Number of phases	1	
Protection	Miniature- / earth leakage circuit breaker	
Total number of groups	2	
Number of poles main switch	2	
Main switch rated current	100 A	
Over voltage protection	No	
Material housing	Steel	
Degree of protection (IP)	IP2XC	
Height	257 mm	
Width	445 mm	
Width in number of modular spacings	16	
Depth	119 mm	
Extension possible	No	
With transparent cover	No	
Lockable	No	
Product Standard/s	BS EN 61439-3	
Frequency	50 Hz	
CE Conformity	Yes	
WEEE Symbol	Yes	
UKCA Conformity	Yes	
Amperage	100 A	
Operating Voltage	230 V	
Type of Current	AC	
Consumer Unit Type	Dual RCD	
Total final circuit modular ways	10	
Busbar type	Flexible	
Main switch rating	100 A	
Main switch final circuit modular ways	0	

RCD 1	80A 30mA type AC
RCD 1 final circuit modular ways	Flexible
RCD 2	80A 30mA type AC
RCD 2 final circuit modular ways	Flexible
Bespoke application	Meter cabinet
Colour RAL	9010

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.



**Electrium Sales Limited**, Walkmill Lane, Cannock WS11 0XE  
01543 455000 [www.electrium.co.uk](http://www.electrium.co.uk) [info@electrium.co.uk](mailto:info@electrium.co.uk)