



- Fully Rated to 10A
- Screw Fixed
- Satin Chrome Finish Rocker
- White Trim

Product Specification Data

Revision Date: 15/10/2021

|  |   |
|--|---|
| Product Standard/s                     | BS EN 60669-1                             |
| Terminal Capacity L&N                  | 4 x 1.0, 3 x 1.5, 1 x 2.5 mm <sup>2</sup> |
| Frequency                              | 50 Hz                                     |
| CE Conformity                          | Yes                                       |
| WEEE Symbol                            | Yes                                       |
| UKCA Conformity                        | Yes                                       |
| Wiring system                          | Two-way switch                            |
| Method of operation                    | Rocker/button                             |
| Assembly arrangement                   | Basic element                             |
| Number of modules (module system)      | 1   |
| Push button switch                     | Yes                                       |
| Number of rockers                      | 1   |
| Mounting method                        | Module frame                              |
| Type of fastening                      | Screw mounting                            |
| With mounting plate                    | No  |
| Material                               | Metal                                     |
| Material quality                       | Other                                     |
| Halogen free                           | Yes                                       |
| Surface protection                     | Other                                     |
| Surface finishing                      | Matt                                      |
| Colour                                 | Stainless Steel                           |
| Illumination                           | No  |
| Function lighting                      | Other                                     |
| Type of lighting                       | LED exchangeable                          |
| Suitable for degree of protection (IP) | IP2X                                      |
| Nominal voltage                        | 250 V                                     |
| Rated current                          | 10 A                                      |
| Connection type                        | Screwed terminal                          |
| Width of device                        | 25 mm                                     |

|   |         |
|---|---------|
| Height of device                        | 55.5 mm |
| Depth of device                         | 31 mm   |
| Built-in depth                          | 20.5 mm |
| Min. depth of built-in installation box | 25 mm   |

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.