List No. 4520/31

CAPITAL

45A Cooker Control Unit With Neon (168mm X 114mm)



- Double Pole Switching
- Neon Indicator
- Safety Shutter System

Product Specification Data	Revision Date: 11/10/2024
Product Standard/s	BS 4177, BS 1363-2
Terminal Capacity L&N	2 x 6.0, 1 x 10, 1 x 16 mm²
Terminal Capacity E	2 x 6.0, 1 x 10.0, 1 x 16.0 mm²
Frequency	50 Hz
LRV Value	74
Printing	Cooker
CE Conformity	Yes
WEEE Symbol	Yes
UKCA Conformity	Yes
Wiring system	2-pole switch
Method of operation	Rocker/button
Assembly arrangement	Control element
Number of modules (module system)	0
Push button switch	Yes
Number of rockers	2
Mounting method	Flush-mounted
Type of fastening	Screw mounting
With mounting plate	Yes
Material	Plastic
Material quality	Other
Halogen free	Yes
Surface protection	Other
Surface finishing	Glossy
Colour	White
Illumination	Yes
Function lighting	Illuminated (on)
Suitable for degree of protection (IP)	IP2X
Nominal voltage	250 V
Rated current	45 A

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.

Connection type	Screwed terminal
Device width	168 mm
Device height	114 mm
Built-in depth	24 mm
Min. depth of built-in installation box	47 mm

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.

Electrium Sales Limited, Walkmill Lane, Cannock WS11 0XE
01543 455000 www.electrium.co.uk info@electrium.co.uk