



- Fully Rated to 10A
- Screw Fixed
- Satin Chrome Finish Rocker
- White Trim

Product Specification Data

Revision Date: 15/10/2021

Product Standard/s	BS EN 60669-1
Terminal Capacity L&N	4 x 1.0, 3 x 1.5, 1 x 2.5 mm ²
Frequency	50 Hz
CE Conformity	Yes
WEEE Symbol	Yes
UKCA Conformity	Yes
Wiring system	Two-way switch
Method of operation	Rocker/button
Assembly arrangement	Basic element
Number of modules (module system)	1
Push button switch	Yes
Number of rockers	1
Mounting method	Module frame
Type of fastening	Screw mounting
With mounting plate	No
Material	Metal
Material quality	Other
Halogen free	Yes
Surface protection	Other
Surface finishing	Matt
Colour	Stainless Steel
Illumination	No
Function lighting	Other
Type of lighting	LED exchangeable
Suitable for degree of protection (IP)	IP2X
Nominal voltage	250 V
Rated current	10 A
Connection type	Screwed terminal
Width of device	25 mm

Height of device	55.5 mm
Depth of device	31 mm
Built-in depth	20.5 mm
Min. depth of built-in installation box	25 mm

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.