



- Fitted With ASTA Approved Fused Link
- Neon Indicator

Product Specification Data

Revision Date: 15/10/2021

Product Standard/s	BS 1363-4
Terminal Capacity L&N	3 x 1.5, 3 x 2.5, 2 x 4.0 mm ²
Terminal Capacity E	1 x 1.5, 1 x 2.5 Solid, 1 x 0.5, 1 x 1.5 Flex mm ²
Frequency	50 Hz
LRV Value	74
Printing	Smoke Detector
CE Conformity	Yes
WEEE Symbol	Yes
UKCA Conformity	Yes
Wiring system	Other
Method of operation	Other
Assembly arrangement	Control element
Number of modules (module system)	0
Push button switch	No
Number of rockers	0
Mounting method	Flush mounted (plaster)
Type of fastening	Screw mounting
With mounting plate	Yes
Material	Plastic
Material quality	Other
Halogen free	Yes
Surface protection	Other
Surface finishing	Glossy
Colour	White
Illumination	Yes
Function lighting	Illuminated (on)
Type of lighting	Not included
Suitable for degree of protection (IP)	IP2X
Nominal voltage	250 V

Rated current	13 A
Connection type	Screwed terminal
Width of device	86 mm
Height of device	86 mm
Depth of device	25 mm
Built-in depth	13 mm
Min. depth of built-in installation box	25 mm

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.