



- 2W Main switch only consumer unit
- Includes a 63A double pole main switch and insulated plug in busbar assembly
- Accepts all Starbreaker miniature final circuit protection devices; MCBs, RCBOs and AFDDs
- Accepts the Starbreaker miniature type 2 SPD, SBT2SPD3W/1
- Constructed from a full metal enclosure with angled visor

| Product Specification Data             |  | Revision Date: 16/06/2022 |
|--|--|---------------------------|
| Mounting method                        | Surface mounted (plaster)                  |                           |
| Number of phases                       | 1  |                           |
| Protection                             | Miniature- / earth leakage circuit breaker |                           |
| Total number of groups                 | 1  |                           |
| Number of poles main switch            | 2  |                           |
| Main switch rated current              | 63 A                                       |                           |
| Over voltage protection                | No   |                           |
| Material housing                       | Steel                                      |                           |
| Degree of protection (IP)              | IP2XC                                      |                           |
| Height                                 | 185 mm                                     |                           |
| Width                                  | 130 mm                                     |                           |
| Width in number of modular spacings    | 4  |                           |
| Depth                                  | 104 mm                                     |                           |
| Extension possible                     | No   |                           |
| With transparent cover                 | No   |                           |
| Lockable                               | No   |                           |
| Product Standard/s                     | BS EN 61439-3                              |                           |
| Frequency                              | 50 Hz                                      |                           |
| CE Conformity                          | Yes  |                           |
| WEEE Symbol                            | Yes  |                           |
| UKCA Conformity                        | Yes  |                           |
| Amperage                               | 63 A                                       |                           |
| Operating Voltage                      | 230 V                                      |                           |
| Type of Current                        | AC   |                           |
| Consumer Unit Type                     | Main switch only                           |                           |
| Total final circuit modular ways       | 2  |                           |
| Busbar type                            | Plug in                                    |                           |
| Main switch rating                     | 63 A                                       |                           |
| Main switch final circuit modular ways | 2  |                           |

Colour RAL

9010

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.

The logo for Electrium, featuring the word "electrium" in a bold, lowercase, sans-serif font. Below the text is a horizontal bar composed of four colored segments: green, red, blue, and yellow.

**Electrium Sales Limited**, Walkmill Lane, Cannock WS11 0XE  
01543 455000 [www.electrium.co.uk](http://www.electrium.co.uk) [info@electrium.co.uk](mailto:info@electrium.co.uk)