



- Single Module 10kA RCBO
- 50A B curve (MCB), 30mA Type A (RCD)
- Neutral & Earth Tail lengths = 1200mm
- For use in Alpha BSII Distribution Boards

Product Specification Data		Revision Date: 29/09/2023
Number of poles (total)	1	
Number of protected poles	1	
Rated voltage	240 V	
Rated insulation voltage $U_i$	264 V	
Rated impulse withstand voltage $U_{imp}$	4 kV	
Rated current	50 A	
Rated fault current	0.03 A	
Leakage current type	A	
Rated short-circuit breaking capacity according to EN 61009	10 kA	
Disconnection characteristic	Undelayed	
Voltage type	AC	
Frequency	50/60 Hz	
Release characteristic	B	
Concurrently switching neutral conductor	No	
With interlocking device	No	
Ambient temperature during operating	-25 - 40 °C	
Width in number of modular spacings	1	
Flush-mounted installation	Yes	
Anti- nuisance tripping version	Yes	
Degree of protection (IP)	IP20	
Connectable conductor cross section solid-core	.75 - 16 mm <sup>2</sup>	
Connectable conductor cross section multi-wired	.75 - 16 mm <sup>2</sup>	
Product Standard/s	IEC 61009-1	
CE Conformity	Yes	
WEEE Symbol	Yes	
UKCA Conformity	Yes	

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.