## SIEMENS

## List No. 5SV3445-6 ALPHA BSII

125A 100mA 4P Type A 5SV3 RCCB

- $I \bigoplus_{i=1}^{n} \bigoplus_$
- Four Pole RCCB
- 125A 100mA
- Type A
- For use with Siemens Alpha BSII Distribution boards

Product Specification Data	Revision Date: 09/02/2024
Number of poles	4
Rated voltage	415 V
Rated current	125 A
Rated fault current	0.1 A
Rated insulation voltage Ui	400 V
Mounting method	DIN rail
Leakage current type	A
Selective protection	No
Frequency	50 Hz
Additional equipment possible	No
With interlocking device	No
Degree of protection (IP)	IP20
Width in number of modular spacings	4
Ambient temperature during operating	40 °C
Connectable conductor cross section multi-wired	35 mm <sup>2</sup>
Connectable conductor cross section solid-core	35 mm <sup>2</sup>
Product Standard/s	BS EN 61008
CE Conformity	Yes
WEEE Symbol	Yes
UKCA Conformity	Yes
Height	85 mm
Width	71 mm
Depth	73 mm

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.

