



- Single module, Miniature AFDD/RCBO combined
- 20A B curve (MCB), 30mA Type A (RCD)
- Single pole with switched neutral
- Neutral Tail lengths = 1200mm
- For use in Alpha BSII Distribution Boards

Product Specification Data

Revision Date: 12/12/2024

Number of poles (total)	2
Number of protected poles	1
Rated voltage	240 V
Rated current	20 A
Rated fault current	0.03 A
Leakage current type	A
Current limiting class	3
Rated short-circuit breaking capacity according to IEC 60947-2	10 kA
Disconnection characteristic	Undelayed
Voltage type	AC
Frequency	50 Hz
Release characteristic	B
Concurrently switching neutral conductor	Yes
With interlocking device	No
Over voltage category	3
Pollution degree	2
Ambient temperature during operating	-25 - 45 °C
Width in number of modular spacings	1
Built-in depth	70 mm
Degree of protection (IP)	IP20
Connectable conductor cross section solid-core	0.75 - 16 mm ²
Connectable conductor cross section multi-wired	0.75 - 16 mm ²
Product Standard/s	IEC 61009-1 / IEC 62606
Frequency	50 Hz
CE Conformity	Yes
WEEE Symbol	Yes
UKCA Conformity	Yes
Amperage	20 A
Height	90 mm

Width	18 mm
Depth	69 mm

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.



Electrium Sales Limited, Walkmill Lane, Cannock WS11 0XE
01543 455000 www.electrium.co.uk info@electrium.co.uk