



- 10 Seconds to 20 Min Time Adjustment
- 4 to 24 metre diameter detection zone
- 1000W Incandescent, 500VA Fluorescent and 500VA Energy saving lamp loads
- 3 to 1000 Lux setting
- Corridor Detection Zone (Centre zone narrows to 6 metre detection zone)

Product Specification Data		Revision Date: 15/10/2021
Product Standard/s	BS EN 60669-1, BS EN 60669-2, BS EN 55015, BS EN 61000-3-2, BS EN 61000-3, BS EN 61547	
Terminal Capacity L&N	2 x 1.5 mm ²	
CE Conformity	Yes	
WEEE Symbol	Yes	
UKCA Conformity	Yes	
Model	Movement Sensor	
Sensor type	Passive infrared	
Scan angle	360 °	
Optimum mounting height	3 m	
Diameter detection range on floor	24 m	
Response value luminosity adjustable	Yes	
Suitable for ceiling mounting	Yes	
Mounting method	Flush mounted (plaster)	
Connection type	Screwed Terminal	
Material	Plastic	
Material quality	Thermoplastic	
Surface finishing	Matt	
Colour	White	
Voltage type	AC	
Frequency	50 Hz	
Nominal voltage	250 V	
Min. switch-on time	10 s	
Max. duty cycle	20 min	
Max. switching power	1000 W	
Temperature	40 °C	
Number of switching zones	1	
Width	90 mm	
Height	90 mm	

Depth	72 mm
Built-in width	53 mm
Built-in depth	33 mm
Built-in length	53 mm
Min. depth of built-in installation box	35 mm

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.