



- Time Adjustment, 30 seconds, 1, 3, 5, 10, 20 and 30 minutes
- 4 to 24 metre diameter detection zone
- 1800W Incandescent, 1100VA Fluorescent and 1100VA Energy saving lamp loads
- 5 to 1000 Lux setting
- Circular Detection Zone

Product Specification Data

Revision Date: 15/10/2021

Product Standard/s	BBS EN 55015, BS EN 61547, BS EN 6100-3-2, BS EN 61000-3-3, BS EN 60669-2-1, BS EN 60669-1
Terminal Capacity L&N	2 x 1.5 mm ²
CE Conformity	Yes
WEEE Symbol	Yes
UKCA Conformity	Yes
Model	Movement Sensor
Sensor type	Passive infrared
Scan angle	360 °
Optimum mounting height	3 m
Diameter detection range on floor	8 m
Response value luminosity adjustable	Yes
Suitable for ceiling mounting	Yes
Mounting method	Flush mounted (plaster)
Connection type	Screwed Terminal
Material	Plastic
Material quality	Thermoplastic
Surface finishing	Glossy
Colour	White
Voltage type	AC
Frequency	50 Hz
Nominal voltage	250 V
Min. switch-on time	30 s
Max. duty cycle	30 min
Max. switching power	1800 W
Temperature	40 °C
Number of switching zones	6
Height	48 mm
Diameter	80 mm

Built-in width	61 mm
Built-in depth	29 mm
Built-in length	61 mm
Built-in diameter	61 mm

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.



Electrium Sales Limited, Walkmill Lane, Cannock WS11 0XE
01543 455000 www.electrium.co.uk info@electrium.co.uk