



- All metal meter cabinet consumer unit
- Plug in insulated busbar assembly
- 4+4W Split load
- 1x 80A 30mA type A RCCB
- 320mm fixing centres

| Product Specification Data | Revision Date: 15/10/2021 |
|----------------------------|---------------------------|
|----------------------------|---------------------------|

| | |
|--|--|
| Mounting method | Other |
| Number of phases | 1 |
| Protection | Miniature- / earth leakage circuit breaker |
| Total number of groups | 2 |
| Number of poles main switch | 2 |
| Main switch rated current | 100 A |
| Over voltage protection | No |
| Material housing | Steel |
| Degree of protection (IP) | IP2XC |
| Height | 257 mm |
| Width | 335 mm |
| Width in number of modular spacings | 12 |
| Depth | 119 mm |
| Extension possible | No |
| With transparent cover | No |
| Lockable | No |
| Product Standard/s | BS EN 61439-3 |
| Frequency | 50 Hz |
| CE Conformity | Yes |
| WEEE Symbol | Yes |
| UKCA Conformity | Yes |
| Amperage | 100 A |
| Operating Voltage | 230 V |
| Type of Current | AC |
| Consumer Unit Type | Split load |
| Total final circuit modular ways | 8 |
| Busbar type | Plug in |
| Main switch rating | 100 A |
| Main switch final circuit modular ways | 4 |

| | |
|----------------------------------|-----------------|
| RCD 1 | 80A 30mA type A |
| RCD 1 final circuit modular ways | 4 |
| Bespoke application | Meter cabinet |
| Colour RAL | 9010 |

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.



Electrium Sales Limited, Walkmill Lane, Cannock WS11 0XE
01543 455000 www.electrium.co.uk info@electrium.co.uk