



- Single module, Uni-Directional RCBO
- 32A C curve (MCB), 30mA Type A (RCD)
- Single pole

Product Specification Data

Revision Date: 07/02/2024

| | |
|--|------------------------|
| Number of poles (total) | 2 |
| Number of protected poles | 1 |
| Rated voltage | 230 V |
| Rated insulation voltage U_i | 400 V |
| Rated impulse withstand voltage U_{imp} | 4 kV |
| Rated current | 32 A |
| Rated fault current | 0.03 A |
| Leakage current type | A |
| Current limiting class | 3 |
| Rated short-circuit breaking capacity I_{cn} according to EN 61009-1 | 6 kA |
| Disconnection characteristic | Undelayed |
| Voltage type | AC |
| Frequency | 50 Hz |
| Release characteristic | C |
| Concurrently switching neutral conductor | No |
| With interlocking device | No |
| Over voltage category | 3 |
| Ambient temperature during operating | -5 - 40 °C |
| Width in number of modular spacings | 1 |
| Built-in depth | 74 mm |
| Flush-mounted installation | No |
| Anti- nuisance tripping version | No |
| Degree of protection (IP) | IP20 |
| Connectable conductor cross section solid-core | .75-16 mm ² |
| Connectable conductor cross section multi-wired | .75-16 mm ² |
| Product Standard/s | IEC 61009-1 |
| CE Conformity | Yes |
| WEEE Symbol | Yes |

| | | |
|-----------------------------------|--|---------------------------|
| Product Specification Data (cont) | | Revision Date: 07/02/2024 |
| UKCA Conformity | | Yes |