



- Single pole MCB, 40A C curve
- Energy limiting Class 3
- Quick release DIN clip
- No miss busbar connection

Product Specification Data		Revision Date: 13/10/2022
Release characteristic	C	
Number of poles (total)	1	
Number of protected poles	1	
Rated current	40 A	
Rated voltage	230 V	
Rated insulation voltage Ui	400 V	
Rated impulse withstand voltage Uimp	4 kV	
Rated short-circuit breaking capacity Icn according to EN 60898 at 230 V	6 kA	
Rated short-circuit breaking capacity Icn according to EN 60898 at 400 V	6 kA	
Voltage type	AC	
Frequency	50 Hz	
Current limiting class	3	
Flush-mounted installation	No	
Concurrently switching neutral conductor	No	
Over voltage category	3	
Additional equipment possible	No	
Width in number of modular spacings	1	
Built-in depth	73 mm	
Degree of protection (IP)	IP20	
Ambient temperature during operating	-5 - 40 °C	
Connectable conductor cross section multi-wired	.75-25 mm²	
Product Standard/s	BS EN 60898-1	
CE Conformity	Yes	
WEEE Symbol	Yes	
UKCA Conformity	Yes	

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.



**Electrium Sales Limited**, Walkmill Lane, Cannock WS11 0XE  
01543 455000 [www.electrium.co.uk](http://www.electrium.co.uk) [info@electrium.co.uk](mailto:info@electrium.co.uk)