List No. 7017/PB

SCREWLESS LOW PROFILE DECORATIVE

6A Triple Pole Fan Isolator Polished Brass Finish



- Screwless Plate
- Triple Pole Switching
- Polished Brass Finish

Product Specification Data	Revision Date: 11/10/2024
Product Standard/s	BS EN 60669-1, BS EN 60947-3
Terminal Capacity L&N	4 x 1.0, 3 x 1.5, 1 x 2.5 mm²
Frequency	50 Hz
Printing	Isolator Symbol, On, Off
CE Conformity	Yes
WEEE Symbol	Yes
UKCA Conformity	Yes
Wiring system	3-pole switch
Method of operation	Rocker/button
Assembly arrangement	Control element
Number of modules (module system)	0
Push button switch	Yes
Number of rockers	1
Mounting method	Flush-mounted
Type of fastening	Screw mounting
With mounting plate	Yes
Material	Metal
Material quality	Other
Halogen free	Yes
Surface protection	Lacquered
Surface finishing	Glossy
Colour	Brass
Illumination	No
Function lighting	Other
Suitable for degree of protection (IP)	IP2X
Nominal voltage	250 V
Rated current	6 A
Connection type	Screwed terminal
Device width	88 mm

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.

Device height	88 mm
Min. depth of built-in installation box	25 mm

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.

Electrium Sales Limited, Walkmill Lane, Cannock WS11 0XE
01543 455000 www.electrium.co.uk info@electrium.co.uk