

List No. 7072/BK CAPITAL / INSTINCT COMMUNICATION & DATA

USB Single 1X2A 5V Output



- Push Fit Module
- Euro Module Solution

Terminal Capacity L&N 1 x 2.5 mm² LRV Value 4 Printing Charge 2A CE Conformity Yes WEEE Symbol Yes UKCA Conformity Yes Assembly arrangement Modular device for domestic switching devices Utilization USB With dust cover No With hinged lid No Outlet direction Straight With imprint No Mounting method Module frame Material Plastic Material quality Thermoplastic Halogen free Yes Surface protection Other Surface finishing Glossy Colour Black Type of fastening Engage (snap) Number of modules (module system) 1 Shielded housing No Width of device 25 mm Betylet of device 34.5 mm Depth of device 34.5 mm	Product Specification Data	Revision Date: 15/10/2021
Printing Charge 2A CE Conformity Yes WEEE Symbol Yes UKCA Conformity Yes Assembly arrangement Modular device for domestic switching devices Utilization USB With dust cover No With hinged lid No Outlet direction Straight With imprint No Mounting method Module frame Material quality Thermoplastic Halogen free Yes Surface protection Other Surface finishing Glossy Colour Black Type of fastening Fastening Number of modules (module system) 1 Shielded housing Width of device 50 mm Depth of device 50 mm	Terminal Capacity L&N	1 x 2.5 mm ²
CE Conformity Yes WEEE Symbol Yes UKCA Conformity Yes Assembly arrangement Modular device for domestic switching devices Utilization USB With dust cover No With hinged lid No Outlet direction Straight With imprint No Mounting method Module frame Material Plastic Material quality Thermoplastic Halogen free Yes Surface protection Other Surface finishing Glossy Colour Black Type of fastening Engage (snap) Number of modules (module system) 1 Suitable for number of connectors 1 Shielded housing No Width of device 25 mm Height of device 50 mm Depth of device 34.5 mm	LRV Value	4
WEEE Symbol Yes UKCA Conformity Yes Assembly arrangement Modular device for domestic switching devices Utilization USB With dust cover No With hinged lid No Outlet direction Straight With imprint No Mounting method Module frame Material Plastic Material quality Thermoplastic Halogen free Yes Surface protection Other Surface finishing Glossy Colour Black Type of fastening Engage (snap) Number of modules (module system) 1 Suitable for number of connectors 1 Shielded housing No Width of device 25 mm Height of device 50 mm Depth of device 34.5 mm	Printing	Charge 2A
UKCA Conformity Yes Assembly arrangement Modular device for domestic switching devices Utilization USB With dust cover No With hinged lid No Outlet direction Straight With imprint No Mounting method Module frame Material Plastic Material quality Thermoplastic Halogen free Yes Surface protection Other Surface finishing Glossy Colour Black Type of fastening Engage (snap) Number of modules (module system) 1 Suitable for number of connectors 1 Shielded housing No Width of device 25 mm Height of device 50 mm Depth of device 34.5 mm	CE Conformity	Yes
Assembly arrangement Utilization USB With dust cover No With hinged lid No Outlet direction Straight With imprint No Mounting method Material Atterial quality Halogen free Surface protection Surface finishing Colour Black Type of fastening Number of modules (module system) Number of connectors Shielded housing With of device Depth of device Depth of device USB Nodular device for domestic switching devices USB Modular device for domestic switching devices No No Modular device for domestic switching devices No No No No Straight No No Other Abrah Call Abrah Surface finishing Colour Black Type of fastening Engage (snap) No No Width of device 25 mm Height of device 34.5 mm	WEEE Symbol	Yes
Utilization USB With dust cover No With hinged lid No Outlet direction Straight With imprint No Mounting method Module frame Material Plastic Material quality Thermoplastic Halogen free Yes Surface protection Other Surface finishing Glossy Colour Black Type of fastening Engage (snap) Number of modules (module system) 1 Suitable for number of connectors 1 Shielded housing No Width of device 25 mm Height of device 50 mm Depth of device 34.5 mm	UKCA Conformity	Yes
With dust coverNoWith hinged lidNoOutlet directionStraightWith imprintNoMounting methodModule frameMaterialPlasticMaterial qualityThermoplasticHalogen freeYesSurface protectionOtherSurface finishingGlossyColourBlackType of fasteningEngage (snap)Number of modules (module system)1Suitable for number of connectors1Shielded housingNoWidth of device25 mmHeight of device50 mmDepth of device34.5 mm	Assembly arrangement	Modular device for domestic switching devices
With hinged lidNoOutlet directionStraightWith imprintNoMounting methodModule frameMaterialPlasticMaterial qualityThermoplasticHalogen freeYesSurface protectionOtherSurface finishingGlossyColourBlackType of fasteningEngage (snap)Number of modules (module system)1Suitable for number of connectors1Shielded housingNoWidth of device25 mmHeight of device50 mmDepth of device34.5 mm	Utilization	USB
Outlet directionStraightWith imprintNoMounting methodModule frameMaterialPlasticMaterial qualityThermoplasticHalogen freeYesSurface protectionOtherSurface finishingGlossyColourBlackType of fasteningEngage (snap)Number of modules (module system)1Suitable for number of connectors1Shielded housingNoWidth of device25 mmHeight of device50 mmDepth of device34.5 mm	With dust cover	No
With imprint Mounting method Module frame Material Material quality Material quality Halogen free Surface protection Surface finishing Colour Black Type of fastening Engage (snap) Number of modules (module system) Suitable for number of connectors 1 Shielded housing Width of device Depth of device Depth of device No Module frame Plastic Thermoplastic Height of device So mm Module frame Nesser Yes Surface finishing Glossy Colour Black I 1 Suitable for number of connectors 1 Suitable for number of connectors 1 Shielded housing No Width of device 34.5 mm	With hinged lid	No
Mounting methodModule frameMaterialPlasticMaterial qualityThermoplasticHalogen freeYesSurface protectionOtherSurface finishingGlossyColourBlackType of fasteningEngage (snap)Number of modules (module system)1Suitable for number of connectors1Shielded housingNoWidth of device25 mmHeight of device50 mmDepth of device34.5 mm	Outlet direction	Straight
MaterialPlasticMaterial qualityThermoplasticHalogen freeYesSurface protectionOtherSurface finishingGlossyColourBlackType of fasteningEngage (snap)Number of modules (module system)1Suitable for number of connectors1Shielded housingNoWidth of device25 mmHeight of device50 mmDepth of device34.5 mm	With imprint	No
Material qualityThermoplasticHalogen freeYesSurface protectionOtherSurface finishingGlossyColourBlackType of fasteningEngage (snap)Number of modules (module system)1Suitable for number of connectors1Shielded housingNoWidth of device25 mmHeight of device50 mmDepth of device34.5 mm	Mounting method	Module frame
Halogen freeYesSurface protectionOtherSurface finishingGlossyColourBlackType of fasteningEngage (snap)Number of modules (module system)1Suitable for number of connectors1Shielded housingNoWidth of device25 mmHeight of device50 mmDepth of device34.5 mm	Material	Plastic
Surface protection Surface finishing Glossy Colour Black Type of fastening Engage (snap) Number of modules (module system) 1 Suitable for number of connectors 1 Shielded housing No Width of device Depth of device 34.5 mm	Material quality	Thermoplastic
Surface finishing Colour Black Type of fastening Engage (snap) Number of modules (module system) 1 Suitable for number of connectors 1 Shielded housing No Width of device 25 mm Height of device 50 mm Depth of device 34.5 mm	Halogen free	Yes
ColourBlackType of fasteningEngage (snap)Number of modules (module system)1Suitable for number of connectors1Shielded housingNoWidth of device25 mmHeight of device50 mmDepth of device34.5 mm	Surface protection	Other
Type of fastening Number of modules (module system) Suitable for number of connectors 1 Shielded housing No Width of device 25 mm Height of device 50 mm Depth of device 34.5 mm	Surface finishing	Glossy
Number of modules (module system)1Suitable for number of connectors1Shielded housingNoWidth of device25 mmHeight of device50 mmDepth of device34.5 mm	Colour	Black
Suitable for number of connectors 1 Shielded housing No Width of device 25 mm Height of device 50 mm Depth of device 34.5 mm	Type of fastening	Engage (snap)
Shielded housing No Width of device 25 mm Height of device 50 mm Depth of device 34.5 mm	Number of modules (module system)	1
Width of device 25 mm Height of device 50 mm Depth of device 34.5 mm	Suitable for number of connectors	1
Height of device 50 mm Depth of device 34.5 mm	Shielded housing	No
Depth of device 34.5 mm	Width of device	25 mm
	Height of device	50 mm
Min denth of huilt in installation hav	Depth of device	34.5 mm
wiii. deptii oi pulit-iii iiistaliatioii pox	Min. depth of built-in installation box	35 mm

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.

