

## List No. 7073 CAPITAL / INSTINCT COMMUNICATION & DATA

USB Dual 2X1A 5V Output



• Euro Module Solution



Terminal Capacity L&N         3 x 2.5 mm²           LRV Value         74           Printing         Charge           CE Conformity         Yes           WEEE Symbol         Yes           UKCA Conformity         Yes           Assembly arrangement         Modular device for domestic switching devices           Utilization         USB           With dust cover         No           With hinged lid         No           Outlet direction         Straight           With imprint         No           Mounting method         Module frame           Material         Plastic           Material quality         Thermoplastic           Halogen free         Yes           Surface protection         Other           Surface finishing         Glossy           Colour         White           Type of fastening         Engage (snap)           Number of modules (module system)         2           Suitable for number of connectors         2           Shielded housing         No           Width of device         50 mm           Height of device         50 mm           Depth of device         35.5 mm           Min. depth of b	Product Specification Data	Revision Date: 15/10/2021
Printing         Charge           CE Conformity         Yes           WEEE Symbol         Yes           UKCA Conformity         Yes           Assembly arrangement         Modular device for domestic switching devices           Utilization         USB           With dust cover         No           With hinged lid         No           Outlet direction         Straight           With imprint         No           Mounting method         Module frame           Material         Plastic           Material quality         Thermoplastic           Halogen free         Yes           Surface protection         Other           Surface protection         Other           Surface finishing         Glossy           Colour         White           Type of fastening         Engage (snap)           Number of modules (module system)         2           Suitable for number of connectors         2           Shielded housing         No           Width of device         50 mm           Depth of device         50 mm           Depth of device         35.5 mm	Terminal Capacity L&N	3 x 2.5 mm <sup>2</sup>
CE Conformity       Yes         WEEE Symbol       Yes         UKCA Conformity       Yes         Assembly arrangement       Modular device for domestic switching devices         Utilization       USB         With dust cover       No         With hinged lid       No         Outlet direction       Straight         With imprint       No         Mounting method       Module frame         Material       Plastic         Material quality       Thermoplastic         Halogen free       Yes         Surface protection       Other         Surface finishing       Glossy         Colour       White         Type of fastening       Glossy         Colour       White         Type of fastening       Engage (snap)         Number of modules (module system)       2         Suitable for number of connectors       2         Shielded housing       No         Width of device       50 mm         Height of device       50 mm         Depth of device       35.5 mm	LRV Value	74
WEEE Symbol         Yes           UKCA Conformity         Yes           Assembly arrangement         Modular device for domestic switching devices           Utilization         USB           With dust cover         No           With hinged lid         No           Outlet direction         Straight           With imprint         No           Mounting method         Module frame           Material         Plastic           Material quality         Thermoplastic           Halogen free         Yes           Surface protection         Other           Surface finishing         Glossy           Colour         White           Type of fastening         Engage (snap)           Number of modules (module system)         2           Suitable for number of connectors         2           Shielded housing         No           Width of device         50 mm           Height of device         50 mm           Depth of device         35.5 mm	Printing	Charge
UKCA ConformityYesAssembly arrangementModular device for domestic switching devicesUtilizationUSBWith dust coverNoWith hinged lidNoOutlet directionStraightWith imprintNoMounting methodModule frameMaterialPlasticMaterial qualityThermoplasticHalogen freeYesSurface protectionOtherSurface finishingGlossyColourWhiteType of fasteningEngage (snap)Number of modules (module system)2Suitable for number of connectors2Shielded housingNoWidth of device50 mmDepth of device50 mmDepth of device35.5 mm	CE Conformity	Yes
Assembly arrangement Utilization USB With dust cover No With hinged lid No Outlet direction Straight With imprint No Mounting method Module frame Material Halogen free Surface protection Surface finishing Colour White Type of fastening Number of modules (module system) Suitable for number of connectors Shielded housing With of device Depth of device  Depth of device  With dust cover No	WEEE Symbol	Yes
Utilization         USB           With dust cover         No           With hinged lid         No           Outlet direction         Straight           With imprint         No           Mounting method         Module frame           Material         Plastic           Material quality         Thermoplastic           Halogen free         Yes           Surface protection         Other           Surface finishing         Glossy           Colour         White           Type of fastening         Engage (snap)           Number of modules (module system)         2           Suitable for number of connectors         2           Shielded housing         No           Width of device         50 mm           Height of device         50 mm           Depth of device         35.5 mm	UKCA Conformity	Yes
With dust cover  With hinged lid  Outlet direction  Straight  With imprint  No  Mounting method  Material  Material quality  Halogen free  Surface protection  Surface finishing  Colour  White  Type of fastening  Nengale (snap)  Number of modules (module system)  Suitable for number of connectors  Shielded housing  With of device  Depth of device  Depth of device  Straight  No  No  Straight  No  Module frame  Module frame  Module frame  Plastic  Thermoplastic  Other  Session  Solossy  Glossy  Colour  White  Type of fastening  Engage (snap)  Number of modules (module system)  2  Suitable for number of connectors  2  Shielded housing  No  Width of device  50 mm  Depth of device  35.5 mm	Assembly arrangement	Modular device for domestic switching devices
With hinged lidNoOutlet directionStraightWith imprintNoMounting methodModule frameMaterialPlasticMaterial qualityThermoplasticHalogen freeYesSurface protectionOtherSurface finishingGlossyColourWhiteType of fasteningEngage (snap)Number of modules (module system)2Suitable for number of connectors2Shielded housingNoWidth of device50 mmHeight of device50 mmDepth of device35.5 mm	Utilization	USB
Outlet directionStraightWith imprintNoMounting methodModule frameMaterialPlasticMaterial qualityThermoplasticHalogen freeYesSurface protectionOtherSurface finishingGlossyColourWhiteType of fasteningEngage (snap)Number of modules (module system)2Suitable for number of connectors2Shielded housingNoWidth of device50 mmHeight of device50 mmDepth of device35.5 mm	With dust cover	No
With imprintNoMounting methodModule frameMaterialPlasticMaterial qualityThermoplasticHalogen freeYesSurface protectionOtherSurface finishingGlossyColourWhiteType of fasteningEngage (snap)Number of modules (module system)2Suitable for number of connectors2Shielded housingNoWidth of device50 mmHeight of device50 mmDepth of device35.5 mm	With hinged lid	No
Mounting methodModule frameMaterialPlasticMaterial qualityThermoplasticHalogen freeYesSurface protectionOtherSurface finishingGlossyColourWhiteType of fasteningEngage (snap)Number of modules (module system)2Suitable for number of connectors2Shielded housingNoWidth of device50 mmHeight of device50 mmDepth of device35.5 mm	Outlet direction	Straight
MaterialPlasticMaterial qualityThermoplasticHalogen freeYesSurface protectionOtherSurface finishingGlossyColourWhiteType of fasteningEngage (snap)Number of modules (module system)2Suitable for number of connectors2Shielded housingNoWidth of device50 mmHeight of device50 mmDepth of device35.5 mm	With imprint	No
Material qualityThermoplasticHalogen freeYesSurface protectionOtherSurface finishingGlossyColourWhiteType of fasteningEngage (snap)Number of modules (module system)2Suitable for number of connectors2Shielded housingNoWidth of device50 mmHeight of device50 mmDepth of device35.5 mm	Mounting method	Module frame
Halogen free Yes Surface protection Other Surface finishing Glossy Colour White Type of fastening Engage (snap) Number of modules (module system) 2 Suitable for number of connectors 2 Shielded housing No Width of device 50 mm Height of device 50 mm Depth of device 35.5 mm	Material	Plastic
Surface protection  Surface finishing  Glossy  Colour  White  Type of fastening  Engage (snap)  Number of modules (module system)  Suitable for number of connectors  Shielded housing  Width of device  For many  Depth of device  Surface frinishing  Glossy  White  Engage (snap)  Engage (snap)  No  Suitable for number of connectors  2  Shielded housing  No  Somm  The ight of device  Somm  S	Material quality	Thermoplastic
Surface finishing Colour White Type of fastening Engage (snap) Number of modules (module system) 2 Suitable for number of connectors 2 Shielded housing No Width of device 50 mm Height of device 50 mm Depth of device 35.5 mm	Halogen free	Yes
Colour Type of fastening Engage (snap) Number of modules (module system) 2 Suitable for number of connectors 2 Shielded housing No Width of device 50 mm Height of device 50 mm Depth of device 35.5 mm	Surface protection	Other
Type of fastening  Number of modules (module system)  2  Suitable for number of connectors  2  Shielded housing  No  Width of device  50 mm  Height of device  50 mm  Depth of device  35.5 mm	Surface finishing	Glossy
Number of modules (module system)2Suitable for number of connectors2Shielded housingNoWidth of device50 mmHeight of device50 mmDepth of device35.5 mm	Colour	White
Suitable for number of connectors 2 Shielded housing No Width of device 50 mm Height of device 50 mm Depth of device 35.5 mm	Type of fastening	Engage (snap)
Shielded housing  No Width of device  50 mm  Height of device  50 mm  Depth of device  35.5 mm	Number of modules (module system)	2
Width of device 50 mm Height of device 50 mm Depth of device 35.5 mm	Suitable for number of connectors	2
Height of device 50 mm  Depth of device 35.5 mm	Shielded housing	No
Depth of device 35.5 mm	Width of device	50 mm
	Height of device	50 mm
Min. depth of built-in installation box 35 mm	Depth of device	35.5 mm
	Min. depth of built-in installation box	35 mm

