



- TP or 4P Switch Disconnecter or Direct Connection incomer options available
- Accepts 3VA11 fixed or adjustable SP or TP MCCBs from 16A to 160A
- Accepts both integral incoming metering (Pulsed output/Modbus or MID) and integral Type 1, Type 2, or Type 1 and 2 surge protection
- Form 3B Type 2 Form of Separation, IP3X with door closed, Icw = 25kA for 1s, Type tested and ASTA certified
- RAL 7035 Grey powder coat finish. Designed and manufactured in the UK to BS EN 61439-3

Product Specification Data

Revision Date: 02/10/2023

Mounting method	Surface mounted (plaster)
Number of phases	3
Number of poles main switch	3
Main switch rated current	250 A
Material housing	Steel
Degree of protection (IP)	IP31
Height	1361 mm
Width	700 mm
Depth	165 mm
Extension possible	Yes
Lockable	Yes
Product Standard/s	BS EN 61439-3
Frequency	50 Hz
CE Conformity	Yes
WEEE Symbol	Yes
UKCA Conformity	Yes
Number of ways (Type 'B' boards)	18
Amperage	250 A
Fault Rating	25
Pole Configuration	TPN
Operating Voltage	400 V
Type of Current	AC
Busbar type	FIXED SOLID COPPER
Colour RAL	7035
Country Of Origin	UK

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.