



- TP or 4P Switch Disconnecter, MCCB or Direct Connection incomer options available
- Accepts 3VA11 fixed or adjustable SP or TP MCCBs from 16A to 160A. Utilising a 8GP12921-0DA25 enclosure allows for the addition of two 200A TP MCCBs
- Accepts both integral incoming metering (Pulsed output/Modbus or MID) and integral Type 1, Type 2, or Type 1 and 2 surge protection
- Form 3B Type 2 Form of Separation, IP3X with door closed, Icw = 35kA for 1s, Type tested and ASTA certified
- RAL 7035 Grey powder coat finish. Designed and manufactured in the UK to BS EN 61439-3

Product Specification Data		Revision Date: 02/10/2023
Mounting method	Surface mounted (plaster)	
Number of phases	3	
Number of poles main switch	3	
Main switch rated current	630 A	
Material housing	Steel	
Degree of protection (IP)	IP31	
Height	1591 mm	
Width	700 mm	
Depth	198 mm	
Extension possible	Yes	
Lockable	Yes	
Product Standard/s	BS EN 61439-2	
Frequency	50 Hz	
CE Conformity	Yes	
WEEE Symbol	Yes	
UKCA Conformity	Yes	
Number of ways (Type 'B' boards)	18	
Amperage	630 A	
Fault Rating	35	
Pole Configuration	TPN	
Operating Voltage	400 V	
Type of Current	AC	
Busbar type	FIXED SOLID COPPER	
Colour RAL	7035	
Country Of Origin	UK	

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.