



- Accessory for Alpha BSII 125A Distribution Boards
- Supplied with Type 2 SPD, 15kA MCB (for SPD protection), cable loom kit & SPD mounting bracket
- 18th edition compliant
- Utilises bottom LH Way for protective MCB
- Nominal Voltage (AC) 230/400

Product Specification Data		Revision Date: 29/09/2023
System configuration DC	No	
System configuration IT	No	
System configuration TN	No	
System configuration TN-C	No	
System configuration TN-C-S	Yes	
System configuration TN-S	Yes	
System configuration TT	Yes	
System configuration other	No	
Number of conductors (without earthing)	4	
Nominal discharge surge current (8/20)	20 kA	
Short-circuit breaking capacity (I _{sc})	25 kA	
Max. continuous voltage AC	350 V	
Max. discharge surge current (8/20)	40 kA	
Mounting method	DIN rail (top hat rail) 35 mm	
Construction size	4 modular spacing	
Max. conductor cross section solid (solid, stranded)	35 mm ²	
Max. conductor cross section flexible (fine-strand)	25 mm ²	
Voltage protection level L-N	1.4 kV	
Voltage protection level N-PE	1.5 kV	
With remote signalling contact	Yes	
Integrated backup fuse	No	
Signalling at the device	Optic	
Category type 2	Yes	
Degree of protection (IP)	IP20	
Product Standard/s	BS EN 61643-11	
Terminal Capacity L&N	25 mm ²	
Terminal Capacity E	25 mm ²	
Frequency	50 Hz	
CE Conformity	Yes	

WEEE Symbol	Yes
UKCA Conformity	Yes

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.



Electrium Sales Limited, Walkmill Lane, Cannock WS11 0XE
01543 455000 www.electrium.co.uk info@electrium.co.uk