



- Form 4b Type 6 (Form of Separation) with 4P devices fitted
- TP or 4P Switch Disconnecter or direct connection incomer options available
- Accepts 3VA11 fixed or adjustable SP, TP or 4P MCCBs from 16A to 160A. Utilising a 8GP1921-0DA26 enclosure with interconnections allows for the addition of two 200A 4P MCCBs
- Accepts both integral incoming metering (Pulsed output/Modbus or MID) and integral Type 1, Type 2, or Type 1 and 2 surge protection
- RAL 7035 Grey powder coat finish. Designed and manufactured in the UK to BS EN 61439-3

Product Specification Data

Revision Date: 15/01/2024

Mounting method	Surface mounted
Number of phases	3
Number of poles main switch	4
Main switch rated current	800 A
Housing material	Steel
Degree of protection (IP)	IP31
Height	1591 mm
Width	703 mm
Depth	240 mm
Extension possible	Yes
With transparent cover	No
Lockable	Yes
Product Standard/s	BS EN 61439-2
Frequency	50 Hz
CE Conformity	Yes
WEEE Symbol	Yes
UKCA Conformity	Yes
Number of ways (Type 'B' boards)	8
Amperage	800 A
Fault Rating	55
Pole Configuration	4P
Operating Voltage	400 V
Type of Current	AC
Busbar type	FIXED SOLID COPPER
Colour RAL	7035
Country Of Origin	UK

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.