



- Form 4b Type 6 (Form of Separation) with 4P devices fitted
- TP or 4P Switch Disconnecter or direct connection incomer options available
- Accepts 3VA11 fixed or adjustable SP, TP or 4P MCCBs from 16A to 160A. Utilising a 8GP1921-0DA26 enclosure with interconnections allows for the addition of two 200A 4P MCCBs
- Accepts both integral incoming metering (Pulsed output/Modbus or MID) and integral Type 1, Type 2, or Type 1 and 2 surge protection
- RAL 7035 Grey powder coat finish. Designed and manufactured in the UK to BS EN 61439-3

Product Specification Data		Revision Date: 15/01/2024
Mounting method	Surface mounted	
Number of phases	3	
Number of poles main switch	4	
Main switch rated current	800 A	
Housing material	Steel	
Degree of protection (IP)	IP31	
Height	1821 mm	
Width	703 mm	
Depth	240 mm	
Extension possible	Yes	
With transparent cover	No	
Lockable	Yes	
Product Standard/s	BS EN 61439-2	
Frequency	50 Hz	
CE Conformity	Yes	
WEEE Symbol	Yes	
UKCA Conformity	Yes	
Number of ways (Type 'B' boards)	12	
Amperage	800 A	
Fault Rating	55	
Pole Configuration	4P	
Operating Voltage	400 V	
Type of Current	AC	
Busbar type	FIXED SOLID COPPER	
Colour RAL	7035	
Country Of Origin	UK	

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.