# List No. 9707

## INGRESS PROTECTED

13A 1 Gang Double Pole Switched Fused Connection Unit With Cord Outlet IP66

- Protected Against Limited Ingress To Dust
- Protected Against Strong Jets of Water

| Product Specification Data | Revision Date: 11/12/2025 |
|---|---|
| Product Standard/s | BS 1363-4 |
| Terminal Capacity L&N | 3 x 1.5, 3 x 2.5, 2 x 4.0 mm² |
| Terminal Capacity E | 3 x 1.5, 3 x 2.5, 2 x 4.0 mm² |
| Frequency | 50 Hz |
| LRV Value | 64 |
| CE Conformity | Yes |
| WEEE Symbol | Yes |
| UKCA Conformity | Yes |
| Wiring system | Other |
| Method of operation | Rocker/button |
| Assembly arrangement | Control element |
| Number of modules (module system) | 0 |
| Push button switch | Yes |
| Number of rockers | 1 |
| Mounting method | Surface mounted |
| Type of fastening | Screw mounting |
| With mounting plate | Yes |
| Material | Other |
| Material quality | Other |
| Halogen free | Yes |
| Surface protection | Other |
| Surface finishing | Matt |
| Colour | Grey |
| Illumination | No |
| Function lighting | Other |
| Suitable for degree of protection (IP) | IP66 |
| Nominal voltage | 250 V |
| Rated current | 13 A |
| Connection type | Screwed terminal |

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.

| | |
|---|---|
| Device width | 96 mm |
| Device height | 130 mm |
| Device depth | 82 mm |

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.

**Electrium Sales Limited,** Walkmill Way, Cannock WS11 0XE
01543 455000 www.electrium.co.uk info@electrium.co.uk