



- Fully Rated to 13A
- Power Indicator
- Test/Reset Functions
- RCD Trip Indicator
- Safety Shutter System

Product Specification Data

Revision Date: 11/10/2024

Product Standard/s	BS 1363-2, BS 7288, BS 5733
Terminal Capacity L&N	3 x 1.5, 3 x 2.5, 2 x 4.0 mm ²
Terminal Capacity E	3 x 1.5, 3 x 2.5, 2 x 4.0 mm ²
Frequency	50 Hz
LRV Value	34
Printing	Test, Reset, 30mA
CE Conformity	Yes
WEEE Symbol	Yes
UKCA Conformity	Yes
Model	British Standard
Number of active contacts (round)	0
Number of active contacts (flat)	3
With signal lamp	Yes
Number of units	1
Number of modules (module system)	0
Number of socket outlets switchable	1
Number of phases	2
Imprint/indication	Data
Connection type	Screwed terminal
With hinged lid	No
With enhanced contact protection	Yes
Label space/information surface	Yes
Colour	Grey
Lockable	No
Insulated mounting	Yes
With function lighting	No
Fault current protection	Yes
Special power supply	No special power supply
Mounting method	Surface mounted

Type of fastening	Mounting with screw
Material	Metal
Material quality	Other
Halogen free	Yes
Surface protection	Other
Surface finishing	Glossy
Anti-bacterial treatment	No
With on/off switch	Yes
Nominal current	13 A
Nominal voltage	250 V
Rated fault current	30 mA
Suitable for degree of protection (IP)	IP2X
Impact strength	IK02
Device width	144 mm
Device height	87 mm
Device depth	44 mm

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.