

- Type A and Type C USB Connection
- Voltage Variation 5V to 12V
- Maximum 20 Watts
- Supports PD, PPS and QC Charging Protocols



**Product Specification Data**

Revision Date: 18/07/2023

|   |   |
|---|---|
| Product Standard/s                      | BS1363-2, BSEN 62368-1                    |
| Terminal Capacity L&N                   | 3 x 1.5, 3 x 2.5, 2 x 4.0 mm <sup>2</sup> |
| Terminal Capacity E                     | 3 x 1.5, 3 x 2.5, 2 x 4.0 mm <sup>2</sup> |
| CE Conformity                           | Yes                                       |
| WEEE Symbol                             | Yes                                       |
| G Mark                                  | Yes                                       |
| UKCA Conformity                         | Yes                                       |
| Operating voltage                       | 250 V                                     |
| Frequency                               | 50 Hz                                     |
| Max. output current                     | 3250 mA                                   |
| Output voltage                          | 12 V                                      |
| Mounting method                         | Flush mounted (plaster)                   |
| Colour                                  | White                                     |
| Min. depth of built-in installation box | 25 mm                                     |

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.