List No. CR1506

INSTINCT

50A Flex Outlet

- Curved Slimline Plate
- Front Fixed and Screw Retained
- Outlet Safety Cap
- Cord Grip

Product Specification Data	Revision Date: 11/10/2024
Product Standard/s	BS 5733
Terminal Capacity L&N	10mm to 16mm mm²
Terminal Capacity E	10mm to 16mm mm²
Frequency	50 Hz
LRV Value	74
CE Conformity	Yes
WEEE Symbol	Yes
UKCA Conformity	Yes
Wiring system	Other
Method of operation	Other
Assembly arrangement	Basic element
Number of modules (module system)	0
Push button switch	Yes
Number of rockers	0
Mounting method	Flush-mounted
Type of fastening	Screw mounting
With mounting plate	No
Material	Plastic
Material quality	Other
Halogen free	Yes
Surface protection	Other
Surface finishing	Glossy
Colour	White
Illumination	No
Function lighting	Other
Suitable for degree of protection (IP)	IP2X
Nominal voltage	250 V
Rated current	50 A
Connection type	Screwed terminal

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.

Device width	86 mm
Device height	86 mm
Device depth	42 mm
Built-in depth	25 mm
Min. depth of built-in installation box	47 mm

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.

Electrium Sales Limited, Walkmill Lane, Cannock WS11 0XE
01543 455000 www.electrium.co.uk info@electrium.co.uk