



- All Upward Facing Terminals
- Full Contact Cable Clamp
- Front Fixed and Screw Retained

| Product Specification Data | | Revision Date: 15/10/2021 |
|--|---|---------------------------|
| Product Standard/s | BS EN 60669-1 | |
| Terminal Capacity L&N | 3 x 2.5, 2 x 4.0, 1 x 6.0 mm ² | |
| Frequency | 50 Hz | |
| LRV Value | 74 | |
| Printing | Hob | |
| CE Conformity | Yes | |
| WEEE Symbol | Yes | |
| UKCA Conformity | Yes | |
| Wiring system | 2-pole switch | |
| Method of operation | Rocker/button | |
| Assembly arrangement | Control element | |
| Number of modules (module system) | 1 | |
| Push button switch | Yes | |
| Number of rockers | 1 | |
| Mounting method | Module frame | |
| Type of fastening | Screw mounting | |
| With mounting plate | No | |
| Material | Plastic | |
| Material quality | Other | |
| Halogen free | Yes | |
| Surface protection | Other | |
| Surface finishing | Glossy | |
| Colour | White | |
| Illumination | No | |
| Function lighting | Other | |
| Type of lighting | Not included | |
| Suitable for degree of protection (IP) | IP2X | |
| Nominal voltage | 250 V | |
| Rated current | 20 A | |

| | |
|---|------------------|
| Connection type | Screwed terminal |
| Width of device | 55 mm |
| Height of device | 25 mm |
| Depth of device | 28 mm |
| Built-in depth | 18.5 mm |
| Min. depth of built-in installation box | 25 mm |

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.