

List No. CR2435 INSTINCT GRID SYSTEM

16A Cord Outlet



• Front Fixed and Screw Retained

Product Specification Data	Revision Date: 15/10/2021
Product Standard/s	BS 5733
Terminal Capacity L&N	4 x 1.0, 3 x 1.5, 1 x 2.5, 1 x 2.5 mm ²
Frequency	50 Hz
LRV Value	74
CE Conformity	Yes
WEEE Symbol	Yes
UKCA Conformity	Yes
Wiring system	Other
Method of operation	Other
Assembly arrangement	Basic element
Number of modules (module system)	1
Push button switch	No
Number of rockers	0
Mounting method	Module frame
Type of fastening	Screw mounting
With mounting plate	No
Material	Plastic
Material quality	Other
Halogen free	Yes
Surface protection	Other
Surface finishing	Glossy
Colour	White
Illumination	No
Function lighting	Other
Type of lighting	Not included
Nominal voltage	250 V
Rated current	16 A
Connection type	Screwed terminal
Width of device	25 mm

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.

Product Specification Data (cont)	Revision Date: 15/10/2	2021
Height of device	55 mm	
Depth of device	20 mm	
Built-in depth	18 mm	
Min. depth of built-in installation box	25 mm	

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.

