

List No. DSF100

100A DP, Insulated Enclosed, Domestic Switch Fuse with 100A Fuse Fitted

- Domestic switch fuse (cw 100A fuse)
- Double pole lockable switch mechanism
- Insulated assembly
- For the connection of sub mains or system extensions

Product Specification Data	Revision Date: 15/10/2021
Version as main switch	No
Version as maintenance-/service switch	Yes
Max. rated operation voltage Ue AC	400 V
Rated operating voltage	230-400 V
Rated permanent current lu	100 A
Conditioned rated short-circuit current Iq	16 kA
Number of poles	2
Motor drive optional	No
Voltage release optional	No
Suitable for distribution board installation	No
Type of control element	Toggle
Interlockable	No
Type of electrical connection of main circuit	Screw connection
Degree of protection (IP), front side	IP20
Product Standard/s	BS EN 60947-3
Terminal Capacity L&N	35 mm ²
Terminal Capacity E	16 mm ²
CE Conformity	Yes
WEEE Symbol	Yes
UKCA Conformity	Yes
Height	139 mm
Width	130 mm
Depth	73 mm

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.

