

List No. DSF100M

100A DP, Metal Enclosed, Domestic Switch Fuse with 100A Fuse Fitted



- Domestic switch fuse (cw 100A fuse)
- Double pole lockable switch mechanism
- All metal enclosure
- For the connection of sub mains or system extensions

roduct Specification Data		Revision Date: 15/10/2021
Version as main switch	No	
Version as maintenance-/service switch	Yes	
Max. rated operation voltage Ue AC	400 V	
Rated operating voltage	230-400 V	
Rated permanent current lu	100 A	
Conditioned rated short-circuit current Iq	16 kA	
Number of poles	2	
Motor drive optional	No	
Voltage release optional	No	
Suitable for distribution board installation	No	
Type of control element	Toggle	
Interlockable	No	
Type of electrical connection of main circuit	Screw connection	
Degree of protection (IP), front side	IP20	
Product Standard/s	BS EN 60947-3	
Terminal Capacity L&N	35 mm ²	
Terminal Capacity E	16 mm²	
CE Conformity	Yes	
WEEE Symbol	Yes	
UKCA Conformity	Yes	
Height	302 mm	
Width	178 mm	
Depth	111 mm	

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.

