

List No. DSF60

100A DP, Insulated Enclosed, Domestic Switch Fuse with 60A Fuse Fitted



- Domestic switch fuse (cw 60A fuse)
- Double pole lockable switch mechanism
- · Insulated assembly
- For the connection of sub mains or system extensions

| roduct Specification Data | | Revision Date: 15/10/2021 |
|---|--------------------|---------------------------|
| Version as main switch | No | |
| Version as maintenance-/service switch | Yes | |
| Max. rated operation voltage Ue AC | 400 V | |
| Rated operating voltage | 230-400 V | |
| Rated permanent current lu | 100 A | |
| Conditioned rated short-circuit current Iq | 16 kA | |
| Number of poles | 2 | |
| Motor drive optional | No | |
| Voltage release optional | No | |
| Suitable for distribution board installation | No | |
| Type of control element | Toggle | |
| Interlockable | No | |
| Type of electrical connection of main circuit | Screw connection | |
| Degree of protection (IP), front side | IP20 | |
| Product Standard/s | BS EN 60947-3 | |
| Terminal Capacity L&N | 35 mm ² | |
| Terminal Capacity E | 16 mm² | |
| CE Conformity | Yes | |
| WEEE Symbol | Yes | |
| UKCA Conformity | Yes | |
| Height | 139 mm | |
| Width | 130 mm | |
| Depth | 73 mm | |

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.

