

## List No. EP073/BK ELYPSE 10AX 3 Gang 1 Way Switch Black Finish

- Smooth and slimline profile
- Clip on front plate for clean screwless aesthetic
- Black Finish

Product Specification Data     Revision Date: 15/10/2021       Product Standard/s     BS EN 60669-1       Frequency     50 Hz       CE Conformity     Yes       UKCA Conformity     Yes       Wiring system     Other       Method of operation     Rocker/button       Assembly arrangement     Basic element       Number of modules (module system)     0       Push button switch     Yes       Number of rockers     3       Mounting method     Flush mounted (plaster)       Type of fastening     Screw mounting       Wirth mounting plate     Yes       Material     Plastic       Material quality     Thermoplastic       Halogen free     Yes       Surface protection     Other       Surface finishing     Other       Colour     Black       Illumination     No       Function lighting     Other       Suitable for degree of protection (IP)     IP2X       Norminal voltage     250 V       Reved current     10 AX       Connection type     Screw		
Frequency50 HzCE ConformityYesUKCA ConformityYesWiring systemOtherMethod of operationRocker/buttonAssembly arrangementBasic elementNumber of modules (module system)0Push button switchYesNumber of rockers3Mounting methodFlush mounted (plaster)Type of fasteningScrew mountingWith mounting plateYesMaterial qualityYesHalogen freeYesSurface protectionOtherSurface finishingGlossyColourBlackIlluminationNoFunction lightingOtherSuitable for degree of protection (IP)IP2XSuitable for degree of protection (IP)IP2XSwitching current for fluorescent lamps10 AX	Product Specification Data	Revision Date: 15/10/2021
NumberYesUKCA ConformityYesUKCA ConformityYesWiring systemOtherMethod of operationRocker/buttonAssembly arrangementBasic elementNumber of modules (module system)0Push button switchYesNumber of rockers3Mounting methodFlush mounted (plaster)Type of fasteningScrew mountingWith mounting plateYesMaterial qualityThermoplasticHalogen freeYesSurface protectionOtherSurface finishingGlossyColourBlackIlluminationNoFunction lightingOtherSuitable for degree of protection (IP)IP2XNominal voltage250 VRated current10 AX	Product Standard/s	BS EN 60669-1
UKCA ConformityYesWiring systemOtherMethod of operationRocker/buttonAssembly arrangementBasic elementNumber of modules (module system)0Push button switchYesNumber of rockers3Mounting methodFlush mounted (plaster)Type of fasteningYesWith mounting plateYesMaterialPlasticMaterial qualityThermoplasticHalogen freeYesSurface protectionOtherSurface finishingGlossyColourBlackIlluminationNoFunction lightingNot includedSuitable for degree of protection (IP)IP2XNominal voltage250 VRated current10 AX	Frequency	50 Hz
Wiring systemOtherMethod of operationRocker/buttonAssembly arrangementBasic elementNumber of modules (module system)0Push button switchYesNumber of rockers3Mounting methodFlush mounted (plaster)Type of fasteningScrew mountingWith mounting plateYesMaterial qualityPlasticHalogen freeYesSurface protectionOtherSurface finishingGlossyColourBlackIlluminationNoFunction lightingOtherType of lightingNot includedSuitable for degree of protection (IP)IP2XNominal voltage250 VRated current10 AX	CE Conformity	Yes
Method of operationRocker/buttonAssembly arrangementBasic elementNumber of modules (module system)0Push button switchYesNumber of rockers3Mounting methodFlush mounted (plaster)Type of fasteningScrew mountingWith mounting plateYesMaterial qualityPlasticHalogen freeYesSurface protectionOtherSurface finishingGlossyColourBlackIlluminationNoFunction lightingOtherSuitable for degree of protection (IP)IP2XNominal voltage250 VRated current10 AX	UKCA Conformity	Yes
Assembly arrangementBasic elementNumber of modules (module system)0Push button switchYesNumber of rockers3Mounting methodFlush mounted (plaster)Type of fasteningScrew mountingWith mounting plateYesMaterial qualityThermoplasticHalogen freeYesSurface protectionOtherSurface finishingGlossyColourBlackIlluminationNoFunction lightingOtherSuitable for degree of protection (IP)IP2XNominal voltage250 VRated current10 ASwitching current for fluorescent lamps10 AX	Wiring system	Other
Number of modules (module system)0Push button switchYesNumber of rockers3Mounting methodFlush mounted (plaster)Type of fasteningScrew mountingWith mounting plateYesMaterial qualityPlasticHalogen freeYesSurface protectionOtherSurface finishingGlossyColourBlackIlluminationNoFunction lightingOtherType of lightingOtherSuitable for degree of protection (IP)IP2XNominal voltage250 VRated current10 ASwitching current for fluorescent lamps10 AX	Method of operation	Rocker/button
Push button switchYesNumber of rockers3Mounting methodFlush mounted (plaster)Type of fasteningScrew mountingWith mounting plateYesMaterialPlasticMaterial qualityThermoplasticHalogen freeYesSurface protectionOtherSurface finishingGlossyColourBlackIlluminationNoFunction lightingOtherType of lightingNot includedSuitable for degree of protection (IP)IP2XNominal voltage250 VRated current10 ASwitching current for fluorescent lamps10 AX	Assembly arrangement	Basic element
Number of rockers3Mounting methodFlush mounted (plaster)Type of fasteningScrew mountingWith mounting plateYesMaterialPlasticMaterial qualityThermoplasticHalogen freeYesSurface protectionOtherSurface finishingGlossyColourBlackIlluminationNoFunction lightingOtherType of lightingOtherSuitable for degree of protection (IP)IP2XNominal voltage250 VRated current10 ASwitching current for fluorescent lamps10 AX	Number of modules (module system)	0
Mounting methodFlush mounted (plaster)Type of fasteningScrew mountingWith mounting plateYesMaterialPlasticMaterial qualityThermoplasticHalogen freeYesSurface protectionOtherSurface finishingGlossyColourBlackIlluminationNoFunction lightingOtherSuitable for degree of protection (IP)IP2XSuitable for degree of protection (IP)ID2XNominal voltage250 VRated current10 ASwitching current for fluorescent lamps10 AX	Push button switch	Yes
Type of fasteningScrew mountingWith mounting plateYesMaterialPlasticMaterial qualityThermoplasticHalogen freeYesSurface protectionOtherSurface finishingGlossyColourBlackIlluminationNoFunction lightingOtherSuitable for degree of protection (IP)IP2XNominal voltage250 VRated current10 AX	Number of rockers	3
With mounting plateYesMaterialPlasticMaterial qualityThermoplasticHalogen freeYesSurface protectionOtherSurface finishingGlossyColourBlackIlluminationNoFunction lightingOtherSuifable for degree of protection (IP)IP2XNominal voltage250 VRated current10 ASwitching current for fluorescent lamps10 AX	Mounting method	Flush mounted (plaster)
MaterialPlasticMaterial qualityThermoplasticHalogen freeYesSurface protectionOtherSurface finishingGlossyColourBlackIlluminationNoFunction lightingOtherSuitable for degree of protection (IP)IP2XNominal voltage250 VRated current10 ASwitching current for fluorescent lamps10 AX	Type of fastening	Screw mounting
Material qualityThermoplasticHalogen freeYesSurface protectionOtherSurface finishingGlossyColourBlackIlluminationNoFunction lightingOtherSuitable for degree of protection (IP)IP2XNominal voltage250 VRated current10 ASwitching current for fluorescent lamps10 AX	With mounting plate	Yes
Halogen freeYesSurface protectionOtherSurface finishingGlossyColourBlackIlluminationNoFunction lightingOtherType of lightingOtherSuitable for degree of protection (IP)IP2XNominal voltage250 VRated current10 ASwitching current for fluorescent lamps10 AX	Material	Plastic
Surface protectionOtherSurface finishingGlossyColourBlackIlluminationNoFunction lightingOtherType of lightingNot includedSuitable for degree of protection (IP)IP2XNominal voltage250 VRated current10 ASwitching current for fluorescent lamps10 AX	Material quality	Thermoplastic
Surface finishingGlossyColourBlackIlluminationNoFunction lightingOtherType of lightingNot includedSuitable for degree of protection (IP)IP2XNominal voltage250 VRated current10 ASwitching current for fluorescent lamps10 AX	Halogen free	Yes
ColourBlackIlluminationNoFunction lightingOtherType of lightingNot includedSuitable for degree of protection (IP)IP2XNominal voltage250 VRated current10 ASwitching current for fluorescent lamps10 AX	Surface protection	Other
IlluminationNoFunction lightingOtherType of lightingNot includedSuitable for degree of protection (IP)IP2XNominal voltage250 VRated current10 ASwitching current for fluorescent lamps10 AX	Surface finishing	Glossy
Function lightingOtherType of lightingNot includedSuitable for degree of protection (IP)IP2XNominal voltage250 VRated current10 ASwitching current for fluorescent lamps10 AX	Colour	Black
Type of lightingNot includedSuitable for degree of protection (IP)IP2XNominal voltage250 VRated current10 ASwitching current for fluorescent lamps10 AX	Illumination	No
Suitable for degree of protection (IP)IP2XNominal voltage250 VRated current10 ASwitching current for fluorescent lamps10 AX	Function lighting	Other
Nominal voltage250 VRated current10 ASwitching current for fluorescent lamps10 AX	Type of lighting	Not included
Rated current 10 A   Switching current for fluorescent lamps 10 AX	Suitable for degree of protection (IP)	IP2X
Switching current for fluorescent lamps 10 AX	Nominal voltage	250 V
	Rated current	10 A
Connection type Screwed terminal	Switching current for fluorescent lamps	10 AX
	Connection type	Screwed terminal



Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.



**Electrium Sales Limited,** Walkmill Lane, Cannock WS11 0XE 01543 455000 www.electrium.co.uk info@electrium.co.uk