



- Smooth and slimline profile
- Clip on front plate for clean screwless aesthetic
- Gold Finish

| Product Specification Data              |                                  | Revision Date: 15/10/2021 |
|---|----------------------------------|---------------------------|
| Product Standard/s                      | BS EN 60669-2-1                  |                           |
| Terminal Capacity L&N                   | 2 x 1.0, 1 x 2.5 mm <sup>2</sup> |                           |
| Frequency                               | 50 Hz                            |                           |
| CE Conformity                           | Yes                              |                           |
| UKCA Conformity                         | Yes                              |                           |
| Wiring system                           | Two-way switch                   |                           |
| Method of operation                     | Turn button                      |                           |
| Assembly arrangement                    | Basic element                    |                           |
| Number of modules (module system)       | 0                                |                           |
| Push button switch                      | Yes                              |                           |
| Number of rockers                       | 1                                |                           |
| Mounting method                         | Flush mounted (plaster)          |                           |
| Type of fastening                       | Screw mounting                   |                           |
| With mounting plate                     | Yes                              |                           |
| Material                                | Plastic                          |                           |
| Material quality                        | Thermoplastic                    |                           |
| Halogen free                            | Yes                              |                           |
| Surface protection                      | Other                            |                           |
| Surface finishing                       | Glossy                           |                           |
| Colour                                  | Gold                             |                           |
| Illumination                            | No                               |                           |
| Function lighting                       | Other                            |                           |
| Type of lighting                        | Not included                     |                           |
| Suitable for degree of protection (IP)  | IP2X                             |                           |
| Nominal voltage                         | 250 V                            |                           |
| Rated current                           | 1.6 A                            |                           |
| Connection type                         | Screwed terminal                 |                           |
| Min. depth of built-in installation box | 35 mm                            |                           |

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.



**Electrium Sales Limited**, Walkmill Lane, Cannock WS11 0XE  
01543 455000 [www.electrium.co.uk](http://www.electrium.co.uk) [info@electrium.co.uk](mailto:info@electrium.co.uk)