

- Smooth and slimline profile
- Clip on front plate for clean screwless aesthetic
- Gold Finish

requency 55 E Conformity Y KCA Conformity Y /iring system C lethod of operation C	Revision Date: 15/10/2021 3S 5733 50 Hz Yes Yes Other
requency 55 E Conformity Y KCA Conformity Y /iring system C lethod of operation C	50 Hz /es /es
E Conformity Y KCA Conformity Y /iring system C lethod of operation C	/es /es
KCA Conformity Y /iring system C lethod of operation C	/es
/iring system C lethod of operation C	
lethod of operation	Dther
ssembly arrangement B	Dther
,	Basic element
umber of modules (module system) 0)
ush button switch N	٧o
umber of rockers 0)
lounting method F	Flush mounted (plaster)
ype of fastening S	Screw mounting
/ith mounting plate Y	/es
laterial P	Plastic
laterial quality	Thermoplastic
alogen free Y	/es
urface protection C	Dther
urface finishing G	Glossy
olour G	Gold
umination N	No
unction lighting C	Dther
ype of lighting N	Not included
uitable for degree of protection (IP)	P2X
	250 V
	15 A
onnection type S	Screwed terminal
	17 mm



Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.



Electrium Sales Limited, Walkmill Lane, Cannock WS11 0XE 01543 455000 www.electrium.co.uk info@electrium.co.uk