



- Smooth and slimline profile
- Clip on front plate for clean screwless aesthetic
- Gold Finish

Product Specification Data

Revision Date: 15/10/2021

Product Standard/s	BS EN 60669-1
Frequency	50 Hz
Printing	Air Conditioner
CE Conformity	Yes
UKCA Conformity	Yes
Wiring system	2-pole switch
Method of operation	Rocker/button
Assembly arrangement	Control element
Number of modules (module system)	0
Push button switch	Yes
Number of rockers	1
Mounting method	Flush mounted (plaster)
Type of fastening	Screw mounting
With mounting plate	Yes
Material	Plastic
Material quality	Thermoplastic
Halogen free	Yes
Surface protection	Other
Surface finishing	Glossy
Colour	Gold
Illumination	Yes
Function lighting	Illuminated (on)
Type of lighting	Not included
Suitable for degree of protection (IP)	IP2X
Nominal voltage	250 V
Rated current	32 A
Connection type	Screwed terminal
Min. depth of built-in installation box	25 mm

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.



Electrium Sales Limited, Walkmill Lane, Cannock WS11 0XE
01543 455000 www.electrium.co.uk info@electrium.co.uk